City of Soledad

Annual Report

General Permit for the Discharge of Storm Water from Small Municipal Separate Storm Sewer Systems (General Permit)

Second Permit Year Report – (2005-2006) December 2006



Prepared by:

Public Works Department

Table of Contents

SECTION 1 - INTRODUCTION	2
Permittee Information	
REPORTING PERIOD	
SECTION 2 - EXECUTIVE SUMMARY	1
Figure A: Areas Annexed During the Second Permit Year	
SECTION 3 - MINIMUM CONTROL MEASURES	6
1. Public Education and Outreach	<i>6</i>
a. BMPs	8
> i. General summary	8
ii. Status of Measurable Goals	
> iii. Appropriateness	
> iv. Effectiveness	8
> v. Proposed Modifications	9
b. Results	
c. Summary	
Figure 1: Location of Markers installed – Second Permit Year	13
2. PUBLIC INVOLVEMENT AND PARTICIPATION	
a. BMPs	
i. General summary	
ii. Status of Measurable Goals	
iii. Appropriateness	
> iv. Effectiveness	
> v. Proposed Modifications	
b. Results	
c. Summary	
3. ILLICIT DISCHARGE DETECTION AND ELIMINATION	
a. BMPs	
i. General summary	
ii. Status of Measurable Goals	
iii. Appropriateness	
> iv. Effectiveness	
> v. Proposed Modifications	
b. ResultsFigure 2: Existing Storm Drainage System – Second Permit Year	
Figure 2: Existing Storm Drainage System – Second Fermit Year Figure 3: Outfalls inspected during the Second Permit Year	
4. CONSTRUCTION SITE STORM WATER CONTROL	
a. BMPs	
≥ i. General summary	
ii. Status of Measurable Goals	
iii. Appropriateness	
> iv. Effectiveness	
> v. Proposed Modifications	
b. Results	
c. Summary	
5. Post-Construction Storm Water Management	
a. BMPs	
> i. General summary	

➢ ii. Status of Measurable Goals	31
iii. Appropriateness	31
> iv. Effectiveness	
> v. Proposed Modifications	32
b. Results	32
c. Summary	
6. POLLUTION PREVENTION AND GOOD HOUSEKEEPING FOR MUNICIPAL OPERATIONS	
a. BMPs	
▶ i. General summary	
➢ ii. Status of Measurable Goals	
> iii. Appropriateness	
iv. Effectiveness	
> v. Proposed Modifications	
b. Results	
Figure 4: Sweeper Route – 2006 (Route A)	
Figure 5: Sweeper Route – 2006 (Route B)	
Figure 6: Storm Water Runoff Sampling Location	
•	
SECTION 4. CERTIFICATION	49
4	
APPENDIX A	50
Brochures English & Spanish - Examples	50
APPENDIX B	53
SOLEDAD TIMES ARTICLES – EXAMPLES (ENGLISH & SPANISH)	53
APPENDIX C	57
SOLEDAD OUTFALLS	57
APPENDIX D	62
STORM DRAIN MARKERS	62
<u> APPENDIX </u>	65
Test Results	65

List of Tables & Graphs

TABLE 1: USED OIL VOLUME AND USED FILTER COLLECTED.	10
TABLE2: OUTFALLS INSPECTED DURING THE SECOND PERMIT YEAR	20
TABLE 3: ANNUAL TESTING RESULTS	38
TABLE #4 MEDIAN GROUND WATER OBJECTIVES PER SALINAS BASIN PLAN	39
GRAPH 1: MEDIAN GROUND WATER OBJECTIVES PER SALINAS BASIN PLAN – CHART#1	39
GRAPH 2: MEDIAN GROUND WATER OBJECTIVES PER SALINAS BASIN PLAN – CHART #2	40

December 2006 iv

City of Soledad Second Annual Report Contact Sheet

Date plan submitted to the Department of Water Resources: 12/06/06

Name of person preparing this plan: Pat Argueta-Serrano, Assistant Engineer

List of City Contacts:

Main City Public Works Telephone:	(831) 678-3963
Main City Public Works Fax:	(831) 678-3965

Clif Price, Public Works Director	Ext. 149	cliff@cityofsoledad.com
Peter Lee., P.E., Associate Engineer	ext. 155	peter@cityofsoledad.com
Pat Argueta-Serrano, Assistant Engineer	ext. 123	pargueta@cityofsoledad.com

Section 1 - Introduction

SECOND ANNUAL REPORT

General Permit for the Discharge of Storm Water from Small Municipal Separate Storm Sewer Systems (General Permit)

Permittee Information

2.0 3.1 4.0 5.0 6.V 7.1	Permittee (Agency N Contact Person: Mailing Address: City, State and Zip C Contact Phone Numb WDID # Have any areas been f YES	C P Sode: Seer: (8	City of Soledad Clifton Price, Public Works Director P.O. Box 156 Soledad, CA 93960 (831) 678-3963 x149 3 27MS04029 the MS4 due to annexation or other legal means? YES NO					
	Outfall Has map		n updated?	Has SWM updat		Receiving Water Name		
		YES	NO	YES	NO			
	Gabilan/Toledo Retention Basin	V		V				
8.		the implementation	on of the Design	Standards in section	D.5 of this Ann			
R	eporting Pe	eriod						
	nis Annual Report 105 and ended or			ear. The Second	d Permit Year	started on September 22,		

Section 2 - Executive Summary

This Second Annual Report is a detailed report on the status of the implementation of the six minimum control measures outlined in the Storm Water Management Plan (SWMP) in the City of Soledad. The purpose of the annual report is to provide an update of all the activities that were completed, the results obtained and the proposed modifications that will be necessary to implement in the third permit year. The report also describes the Best Managements Practices (BMPs) that were not implemented during the first permit year but were completed and fully implemented during the second permit year. The annual report covers the period from September 22, 2005 through September 21, 2006.

New areas were annexed into the City of Soledad within this reporting period. One segment of the annexed area created construction activities that were monitored by the Public Works Department during the second permit year. Figure A illustrates the annexed area. Every project that disturbs either one acre of land or more receives information about the SWMP and BMPs that are required to be implemented during the construction activities that will be monitored and enforced by the City. Only one project met the threshold of one acre or more during this period.

Public education and public information have been developed and conducted during this reporting period and community educational activities on storm water pollution prevention will continue to be implemented and offered during the rest of the permit years. For instance, the first educational bilingual brochures were created and were available at the City Hall counters and the City of Soledad Public Library. Three bilingual storm water articles were developed and published in the quarterly Soledad Times newspaper. Each issue of the Soledad Times distributes approximately an average of 6,000 copies each quarter and covers the entire City. The City of Soledad storm water website continues to be updated with information and references to storm water pollution reduction activities. The web page can be visited at http://www.cityofsoledad.com/departments/publicwrks.

The first storm water presentations to local community groups were also accomplished during the summer of the second permit year. Educational materials were distributed at those presentations. Topics covered during the presentation included explanations of purpose and objectives of the City's SWMP and provided information and ideas about storm water pollution prevention that each resident can implement in their home. The workshops included a power point presentation and a display of the stenciling materials that the City installed and also plans to install in the future. Volunteer assistance was requested at those meetings.

The City of Soledad storm water drainage system map was completed during the second permit year. The new system in the subdivision that started its construction this permit year was also incorporated to the new storm map. The creation of the storm drainage map has assisted the Public Works Department to investigate complaint regarding storm water pollution. The affected areas were located and recorded for future investigations. Ten new storm drain markers were installed, and the new 2006 City of Soledad Design Standards and Standard Specifications included in its requirements the installation of storm drain markers in new projects.


The first storm water training classes were arranged and completed this permit year. The Public Works Staff received training on how to report illicit discharges noticed in the City. The first hazardous material training class between the Public Works Department, the Police Department and the Fire Department was also arranged and completed during the summer of the second permit year.

The City of Soledad is subject to Attachment 4 (Supplemental Provisions) of the General Permit. Compliance with the supplemental provisions has been achieved during the second permit year.

The City continues implementing pollution prevention in their daily activities, such as sweeping, cleaning of the storm drainage inlets, storing properly hazardous material etc. The sweepers' schedules are illustrated in Figures 3 and 4.

This year pictures were taken for the first time to illustrate the conditions of the outfalls when they were inspected. The pictures can be found in Appendix C. The first annual testing was conducted this permit year. The results obtained for the first test will be used as the baseline for future comparisons. Six sampling locations were selected for this first annual testing program.

The activities for the Second and First permit year have been completed and some modifications in the SWMP will be necessary in the next permit year. The proposed modifications are explained in detail in the report. The results obtained during the second permit year will increase the effectiveness of the best management practices that will be created and implemented on the third permit year.



Section 3 - Minimum Control Measures

1. Public Education and Outreach

The City is reporting the status and effectiveness of BMPs and measurable goals by completely answering the questions that follow includes any proposed modifications to the SWMP and anticipated changes to the schedule. Tables are provided as well as use narrative sections to highlight information.

ВМР	Description	Status					
		Implemented	Not Applicable	Modified	Effective	Unknown	Not Effective
1.1 Utility Billings	Storm water messages reaching every residence and business in the City to effectively increase awareness of how seasonal activities can contribute to water pollution and to call out safeguards that aim to reduce pesticides, salinity/TDS/chlorides, and sediment/siltation, and other pollutants as appropriate and specific to the City.	√					
1.2 Web site for storm water information	Website developed for widespread access to storm water information, programs, and activities.	V					
1.3 Media advertisements - Television	Storm water advertisements regularly broadcast. Broadcasts will cover a wide range of topics, such as: - How pollution on land can lead to receiving water - Where used motor oil can be recycled, and why it's important to do so - How restaurant kitchen staff can prevent storm drain pollution	V					
1.4 Media advertisements - Newspaper	No-cost storm water advertisements reaching a broad audience via printed media	√					

ВМР	Description		Status				
		l mple mente d	Not Applicable	Modlfied	Effective	Unknown	Not Effective
1.5 Brochures or fact sheets for general public and specific audiences	Storm water pollution prevention information readily available to residents, students, business owners, designers, developers, & contractors at City Hall, the library, cleanup events, and classroom educational visits.	V					
1.6 Publish use of City Hall phone number for Storm Water Hotline for information and citizen reporting of polluters	Provide a clear-cut means for the public to contact the City and report illicit discharges and illicit dumping.	V					
1.7 Proper disposal of household hazardous wastes	Facility (ies) provided for the public to dispose of hazardous materials that may otherwise be dumped illegally. Goal is to reduce amount of trash, household chemicals, pesticides, etc. entering the City's storm water system.	√					
1.8 Used Oil Recycling	Facility(ies) provided for the public to dispose of used motor oil in an effort to reduce the amount of petroleum hydrocarbons and other chemicals entering the City's storm water system due to illegal dumping.	V					
1.9 Storm drain stenciling	Notice to community citizens regarding storm water pollution prevention at point of possible entry to storm drain system. Expected reduction in amount of trash and motor oil entering the City's storm sewer system.	V					
1.10 Participation in Regional Storm Water Information Exchange	The City will participate in regional storm water information exchange meetings to enhance their own implementation efforts, and to build upon the lessons learned from other municipalities.	V					

a. BMPs

i. General summary

The Public Education and Outreach activities for the second permit year have been implemented as originally planned. The pending Best Management Practices (BMPs) that were not completed during the first permit year were completed during the second permit year.

For instance, public information articles were advertised in the quarterly Soledad Times newspaper and bilingual educational brochures were created and distributed. Appendix A shows an example of the brochure created and Appendix B shows copies of the Soledad Times newspaper that were created during the second permit year. The City web page has been updated and new links have been added. The City storm water website will be updated and evolved as the City's program evolves. The website can be found at: http://www.cityofsoledad.com/departments/publicwrks/index.cfm.

ii. Status of Measurable Goals

100% of the second permit year's measurable goals have been achieved.

iii. Appropriateness

The minimum control measures implemented during the second permit year were appropriated for the City Storm Water Management Program. The bilingual messages created for the local television channel, the brochures and the quarterly newspaper articles provided the opportunity to reach a larger sector of the City's population.

iv. Effectiveness

The goals achieved during the second permit year cannot be adequately measured at this time. Although several forms of communications to reach the public have been created and implemented during the second permit year, it is difficult to measure the effect on the people's behavior without having more data.

v. Proposed Modifications

Modifications proposed for the third permit year included changes on BMP 1.1 and BMP 1.10.

BMP 1.1

The Utility Billings will not be used as educational media for the rest of the permit. Bilingual messages cannot be displayed on utility bills because only 36 characters can be displayed. This limited spaced forced the City staff to alternate the messages and present each message in one language. This type of advertisement created unhappy mixed emotions among a small sector of the City who were not happy to see Spanish messages without the translation in English. In lieu of this BMP, the educational information will be displayed only in brochures, the local television channel, the City web page, and in the Soledad Times Newspaper.

BMP 1.10

The participation in regional storm water information exchanges will be limited to the available meetings in the region. During the second permit year, the City only attended one meeting because the Salinas River Channel Coalition only had one annual meeting.

b. Results

Results of information collected and analyzed are included below.

Table 1 shows the volume of used oil and number of used filter units collected from the Residential areas by Tri-Cities Disposal & Recycling during the months of September 2005 to September 2006. According to the information collected from Tri-Cities Disposal & Recycling, the company does not collect used oil or used filter units from multi family account, commercial and industrial areas because the grant provided by the County only covered the residential areas

In addition, determining the percentage of the customers that use this service is a difficult task because Tri-Cities Disposal & Recycling does not know the number of vehicles that each resident owns and frequency of the oil change in each vehicle.

Table 1: Used Oil Volume and Used Filter Collected

	Used Oil	Used Filters
Month		
S	gallons	each
Sep-05	112.0	90.0
Oct-05	71.0	65.0
Nov-05	98.0	96.0
Dec-05	116.0	107.0
Jan-06	81.0	68.0
Feb-06	93.0	72.0
Mar-06	113.0	88.0
Apr-06	142.5	106.0
May-06	137.5	114.0
Jun-06	146.5	133.0
Jul-06	66.0	36.0
Aug-06	180.0	159.0
Sep-06	178.5	86.0

c. Summary


Below is a summarization of the storm water activities planned during the next reporting cycle (including an implementation schedule).

The chart below outlines the City's next reporting cycle of storm water activities that will be implemented during the third permit year.

	Proposed	Modified?		Schedule		
BMP	Measurable Goal	YES	NO	Complete	Ongoing Implementation	
	Measurable Coal			this year		
1.1 Utility Billings	Messages distributed quarterly Permit Years 1-5 MG: Run four messages/yr	٧		Yes.	For the Third Permit Year, this BMP will not be implemented. Only 36 characters can be displayed in the utility bill, and this limited space made impossible for the City staff to display bilingual messages in the bills. As a result, during the second permit year, four messages were displayed in the utility bills, two English and two in Spanish to reach the entire City's population. However, this type of advertisement created mixed emotions among some of the City residents who did not wanted to see messages displayed only in Spanish. To	
					avoid more complaints, it was decided to focus the educational information to the brochures, the local TV channel, and the Soledad Times Newspaper because the	
					messages can be displayed in English and Spanish at the same time.	

	Proposed	Modif	ied?	Schedule	
BMP	Measurable Goal	YES	NO	Complete this year	Ongoing Implementation
1.2 Web site for storm water information	MG: Current storm water information placed on website, number emails and hotline use documented		V	Yes.	Ongoing throughout permit term.
1.3 Media advertisements - Television	Permit Year 1: Legwork to determine req'ts of broadcasting text ad; develop ads by summer of First Permit Year MG: Ads developed		V	Yes.	Ongoing throughout permit term.
1.4 Media advertisements – Newspaper	Permit Year 1: Negotiations with Soledad Bee for PSA by Summer of First Permit Year MG: Ad size and running frequency with Soledad Bee determined	V		V	The quarterly Soledad Times Newspaper has been used mainly to advertise the storm water ads. The first add was advertised last February 2006. The Soledad Times Newspaper is a free service and Four ads per year will be advertised by using this newspaper.
1.5 Brochures or fact sheets for general public and specific audiences	Permit Year 1: Coordinate with library and City Hall on material dispensers (contents & display location) by Summer of Permit Year 1 MG: Storm water displays choreographed		V	1	Ongoing throughout permit term .
1.6 Publish use of City Hall phone number for Storm Water Hotline for information and citizen reporting of polluters	Hotline advertised immediately upon development of Storm Water section of the City's website, in Permit Year 1. MG: Hotline voice mailbox set up (See also BMP 3.2)		V	V	Ongoing throughout permit term. Hotline phone number has been advertised in the City web page, the quarterly Soledad Times newspaper and in educational brochures.

	Proposed	Modif	ied?	Schedule	
BMP	Proposed Measurable Goal	YES	NO	Complete	Ongoing Implementation
1.7 Proper disposal of household hazardous wastes	Locations added to storm water section of City website in Permit Year 1 and updated asneeded if information changes. MG: Min. 2 existing locations for hazardous materials disposal listed on City website		√	this year √	Ongoing throughout permit term. Locations of disposal places have been advertised in the City web page, the quarterly Soledad Times newspaper and in educational brochures.
1.8 Used Oil Recycling	Permit Year 1: Determine existing efforts of a nearby recycling facility to advertise their facility by Summer of First Permit Year MG: Facility's existing advertising media & frequency determined. Facility advertised on City storm water website		V	V	Ongoing throughout permit term. Locations of disposal places have been advertised in the City web page, the quarterly Soledad Times newspaper and in educational brochures.
1.9 Storm drain stenciling	Permit Year 1: Procurement of stencil(s) to display appropriate message by end of Summer first Permit Year MG: Stencil(s) chosen		V	1	Ongoing throughout permit term. Ten storm drain markers were installed. Figure 1 shows the location of the markers that were installed during the second permit year.
1.10 Participation in Regional Storm Water Information Exchange	The City will participate in a minimum of one regional storm water information exchange meeting per quarter. MG: Attend min. 1 meeting/quarter	√		V	The Salinas River Channel Coalition had one annual meeting, and it was done during the month of April. No more meetings were scheduled, but the City staff received continues email regarding the status of any pending issue. If the Coalition has pending issues, more meetings are arranged. Last year, the City attended two meetings. The meetings are attended either by the Mayor, the City Manager, or by the Public Works Director. In addition, the City receives educational emails from the California Storm water Quality Association (CASQA, and currently, the City still searching for other local associations to be members. Although there are other associations in the County, the City cannot become member of each one due to geographic location and different concerns that are not affecting the City.



2. Public Involvement and Participation

ВМР	Description	Status					
		Implemented	Not Applicable	Modlfied ¹	Effective	Unknown	Not Effective
2.1 Educational and volunteer programs for school-age children and community groups	Community participation and education on storm water pollution prevention. Visible, interactive activities for storm system cleanup and protection, encouraging a vested interest in keeping pollution from entering City's storm sewer system.	V					
2.2. Community Feedback	To solicit feedback and participation from the community. Community awareness that the City encourages and expects awareness on a City-wide level. Workshops will be held prior to the start of the rainy season in order to alert citizens to methods of preventing pollutants from entering runoff, and prior to submittal of the annual report in order to incorporate community feedback into the report.		√ 3rd Yr				

a. BMPs

i. General summary

During the second permit year, the City participated in two public meeting with two community groups. The first public meeting was held on September 6, 2006 with the Lionesses Club, and the second meeting with the Rotary Club on September 11, 2006. During the meeting, brochures were distributed with storm water pollution prevention information and the Storm Water Management Plan was explained to both groups.

The community program called "SCOPE" that was mentioned in the original Storm Water Management Plan document is no longer available. Many of the staff that worked during the development of the Plan are not working anymore with the City. As a result, the recruiting of volunteers started from zero.

ii. Status of Measurable Goals

100% of the second permit year's measurable goals have been achieved.

iii. Appropriateness

The minimum control measure implemented during the second year of the permit was an appropriate beginning for the Plan.

The questions raised during the meetings will assist the City to prepare for the first community workshop.

iv. Effectiveness

Determining the overall effectiveness of the implemented BMP is not possible during the second permit year. Although during the two meetings the people showed interested in stopping pollution, no volunteers groups were formed or contacted the City.

> v. Proposed Modifications

Modification proposed for the third permit year includes the change in the presentation of the first community workshop and the volunteer assistance.

First community workshop will be offered during the month of December due to several activities from the Public Works Department that limited the organization of the workshop.

The clean up activities will be limited to the installation of curb markers on existing catch basis, in stenciling the catch basis, and in monitoring the conditions of the existing drainage system. Cleaning the catch basis is excluded from the volunteer's activities because this activity involved the use of heavy equipment. We also contacted a local community leader regarding this activity and the recommendation was to limit the volunteer activities to the curb markers installation, stenciling the inlets and monitoring the conditions of the existing drainage system because the involvement of heavy equipment and liability.

b. Results

Results of information collected and analyzed are included below.

Since the community program "SCOPE" is not available, the City currently does not have any volunteers. After the two meetings with the local groups, none has approached the City. There is no official list of people willing to participate in the volunteer activities.

c. Summary

Below is a summarization of the storm water activities planned during the next reporting cycle (including an implementation schedule).

The chart below outlines the City's next reporting cycle of storm water activities that will be implemented during the third permit year.

	Drangad	Modif	ied?	Schedule	
BMP	Proposed Measurable Goal	YES	NO	Complete this year	Ongoing Implementation
2.1 Educational and volunteer programs for school-age children and community groups	Permit Year 2: Contact with community groups to encourage participation by Spring Second Permit Year. MG: List of community groups interested in participating documented.	٧		√ √	Although the City contacted and performed storm water pollution presentations to some local community groups; such as the Lioness Club and the Rotary Club; the City did not obtained an official list of people willing to participate in a clean out. Cleaning the storm drain system is a physical work that required the used of special tools; therefore, during our presentations we asked for volunteers to help the City to stencil the catch basins, and to report any illicit discharged in order to stop the polluters. We are also planning to use school groups to help us to stencil the catch basins.
2.2. Community Feedback	Permit Year 3: Develop community vision workshop agenda and hold first workshop by Fall of Third Permit Year. MG: Hold one workshop/yr, quantity attendees documented.		V	No.	Community workshop will be developed during the Third Permit Year.

3. Illicit Discharge Detection and Elimination

ВМР	Description			Sta	tus		
		l m p l e m e n t e d	Not Applicable	Modlfied	Effective	Unknown	Not Effective
3.1 Storm drain system map	Inventory of storm drain inlets and infrastructure for better monitoring, maintenance, and cleaning.	√					
3.2 Storm Drain Outfall Inspections	To offer a means by which the City can track outfall conditions and link signs of pollution at the outfall with known or reported illicit discharges upstream of the outfall structure in the storm system.	V					
3.3 Illegal dumping reporting	Public awareness that the City is serious about preventing illegal dumping and discharges by encouraging people to report illicit discharge or dumping activities, and by promptly responding to these reports. An established system of reporting allows the City to a) investigate, b) track, and c) enforce these potential threats to water quality. (See also BMPs 3.4 & 3.5.)	√					
3.4 Illegal dumping documenting and monitoring	Inventory of the frequency, type, and location of illicit discharges to distinguish which pollutants are entering the City's storm drain system, what the possible sources are, and with what frequency the dumping or discharge occurs. Expected decrease in response time after reports are filed.	√					
3.5 Illegal dumping investigations and tracking of "Hot Spots"	Reduction in illicit discharges, especially in areas found to be impacted most severely by pollutants of concern.	√					
3.6 Adopt ordinance, including an enforcement mechanism	Develop Storm Water Ordinance on April 6, 2005 to provide the legal authority for regulating illegal discharge and provide for enforcement activities.	√					

ВМР	Description			Sta	tus		
		Implemented	Not Applicable	ModIfied ¹	Effective	Unknown	Not Effective
3.7 Sanitary sewer system map	Inventory of sewer infrastructure for proximity information related to storm drainage infrastructure to identify and reduce discharges from any illicit sanitary sewer connections or sewer overflows.	V					
3.8 Watch list for illicit connections	Awareness for City employees of those businesses that may be the source of potential illicit discharges into the storm drain system. Industry awareness that various facilities are subject to random investigations for illicit discharges. Result is reduced sources of non-storm water pollutant loading into the City's system.		√ 3rd Yr				
3.9 Industrial/business connections	Accountability for undocumented connections to storm drain system. Compliance encouraged. Objective is to identify unknown connections and assess if the connections are to be disconnected or may remain in service (depending upon the composition of the discharge, i.e. storm water or non-storm water). As a result, the City will have a more complete map of points of storm water discharge into the City's system, and/or reduce sources of non-storm water pollutant loading into the City's system.		√ 3rd Yr				
3.10 Review and Identification of Non- Storm Water Discharges	Objective is to determine other significant sources of pollutants that enter the storm drain system, and work toward reducing them through public education and other BMPs appropriate for the discharges determined to be significant by the RWQCB Executive Officer.		√ 3rd Yr				

a. BMPs

i. General summary

During the second permit year, the BMPs that were not completed during the first permit year were completed. The storm drain system map, for example, was completed and the new map showed also the new system that was installed in Miravale II, Unit I, a new subdivision that is currently under construction. The new electronic drawing has identified each outfall and its tributary areas. Figure 2 shows the storm drain system map. Illicit discharges reports throughout the City have been responded to and cleaned up and responsible parties were identified and corrective actions were taken by implementing the storm water ordinance developed during the first permit year. No sewer overflows were discovered or reported last year to identify "hot spots" that may require rehabilitation or repairs.

ii. Status of Measurable Goals

All the second year's measurable goals have been achieved in their entirety.

iii. Appropriateness

The creation of the ordinance during the first permit year allows the City to address illicit discharges during the rest of the permit. The storm water ordinance allows the City to enforce illicit discharge laws when illicit discharges were reported during the second permit year. The development of the storm drain system map allows the City to find illicit discharges when they occur and to locate areas that will be affected when an illicit discharge occurs.

iv. Effectiveness

Continuing updating the storm drain map will assist the City in tracking down polluters and identifying areas where illicit sanitary sewer connections may exist. The inspections of the outfalls allow the City to detect what areas of the City are affected by polluters and would required more inspection. Monitoring illegal dumping reports by using the updated City's storm drain system map allows the City to locate "hot spots" or problematic areas.

v. Proposed Modifications

No modifications are proposed at his time.

b. Results

Results of information collected and analyzed are included below.


The new sanitary sewer system's electronic AutoCAD drawings for Miravale II, Unit I, the new subdivision that started last April, were obtained and added to the existing sanitary sewer AutoCAD drawings and will be incorporated to the Geographic Information System (GIS) existing sewer system map.


Six illegal discharges were documented during the second permit year. Inspections were done to the reported areas, and two warning letters were sent, one to a local industry and one to a construction company. Letters were sent and corrective measures were implemented to avoid another illicit discharge. During working hours, the public can call (831) 678-3963 to report any problem inside the City limits, they can also can leave message at the hot line at (831) 678 extension 121. Every morning the City staff member monitors the hotline.

Each outfall was inspected during the second permit year, and Table 2 list the outfalls that were inspected, Figure 3 illustrates the location of the outfalls, Appendix C shows the photos taken during the inspection that illustrate the conditions of the outfalls.

Table2: Outfalls inspected during the Second Permit Year

Outfall	Outfall	Basin	Inspection
Number	Name/Location	Туре	Date
1	Basin pond along Gabilan Street/Toledo St	Retention	8/30/2006
2	Santana Park along Prado and Gabilan Street	Detention	8/30/2006
3	Veterans Memorial Park at Gabilan Street/San Vicente	Detention	8/30/2006
3	vectans wemonan raik at Gabrian Street/San vicente	Detention	0/30/2000
4	Basin pond at Front Street/West Street	Retention	8/30/2006
5	City Treatment Plant Area – headwork		8/30/2006
6	Nestles Road Outfall – Front & Nestles		8/30/2006
7	Basin pond at Market Street/San Vicente	Detention	8/30/2006





c. Summary

Briefly summarize the storm water activities you plan to undertake during the next reporting cycle (including an implementation schedule). If you propose activities that differ from those originally proposed in the approved SWMP, provide justification.

The chart below outlines the City's next reporting cycle of storm water activities that will be implemented during the third permit year.

		Modif	ied?	Schedule	
BMP	Proposed Measurable Goal	YES	NO	Complete	Ongoing Implementation
				this year	
3.1 Storm drain system map	Permit Year 1: Update storm water map with existing known facilities by Summer First Permit Year MG: Map updated		V	√ √	Continue to update the existing storm drain system map to show new projects as they are constructed
3.2 Storm Drain Outfall Inspections	Permit Year 1: Establish baseline conditions for all outfall structures MG: 100% outfall structures inspected, logged, and photographed		√	√	
3.3 Illegal dumping reporting	Permit Year 1: Hotline for reports of illegal dumping in place and log begun documenting each report MG: Hotline voice mailbox set up, number of calls documented		1	V	
3.4 Illegal dumping documenting and monitoring	Permit Year 2: Numeric & qualitative analysis of all reports documented over the first Permit Year. Development of criteria for consideration of "hot spots." MG: Discharge types documented, number of discharges tracked & cleaned up, documented. "Hot spot" criteria determined.		1	√	
3.5 Illegal dumping investigations and tracking of "Hot Spots"	Permit Year 2: Initiate formal investigations & tracking for "hot-spots" by Oct. of Second Permit Year MG: Number investigations/hot spot established, tracking records developed		√	V	
3.6 Adopt ordinance, including an enforcement mechanism	Complete ordinance by Dec. of First Permit Year. MG: Ordinance adopted		V	Adopted on April 6, 2005	

		Modif	ied?	Schedule	
BMP	Proposed Measurable Goal	YES	NO	Complete	Ongoing Implementation
				this year	
	Permit Year 1: Update sewer		,	,	
3.7 Sanitary sewer	map with existing known		√	V	
system map	facilities by Summer First Permit				
	Year				
	MG: Map updated				
	Permit Year 3: All City		,	No.	Implementation will start
3.8 Watch list for illicit	businesses to be grouped and		√		during the third year of the
connections	profiled for potential of having				permit
	non-stormwater discharges into				
	the City storm sewer system.				
	MG: 100% businesses profiled				
	and "watch list" created.				
3.9 Industrial/business	Permit Year 3: Letter mailed out		,	No.	Implementation will start
connections	to all businesses by Oct of Third		√		during the third year of the
	Permit Year				permit
	MG: Letter sent to 100%				
	businesses.				
3.10 Review and	Permit Year 3: Plan developed		١,	No.	Implementation will start
Identification of Non-	MG: Breakdown of planned		√		during the third year of the
Storm Water	evaluation technique for each				permit
Discharges	discharge developed.				

4. Construction Site Storm Water Control

ВМР	Description	Status					
		l m p l e m e n t e d	Not Applicable	ModIfied ¹	Effective	Unknown	Not Effective
4.1 Regulatory mechanism for controlling polluted runoff from construction sites.	To enforce compliance in developing and implementing erosion and sediment controls from construction site storm water runoff.	V					
4.2 Construction site BMPs for controlling erosion & sediment at site	To ensure effective and appropriate use of available erosion and sediment control measures on an individual construction site basis.	V					
4.3 SWPPP Requirements and Guidelines	Formalized legal responsibility and accountability for effectively reducing sediment, erosion, and on-site chemical runoff associated with construction operations.	V					
4.4 Tracking of sites >1 acre with associated erosion & sediment control measures	Tracking mechanism for ensuring 100% of all sites are accounted for in implementing the associated BMPs as described and approved in their SWPPP.	√					
4.5 Inspections for sediment & erosion control	All construction sites ≥1 acre inspected, prioritized, and tracked by the City. Prioritization will give more attention to those sites that may have the greatest impact to compromising water quality to ensure the Contractor is held accountable for the BMPs that require implementation during construction.	√					
4.6 Penalties for non- compliance with runoff control measures	All construction sites ≥1 acre tracked and, when necessary, penalized for non-compliance. Provides incentives to Contractor for proper implementation of construction site BMPs, thereby reducing sediment and construction waste chemicals that would otherwise enter the City's storm drain system from these sites.	√					

ВМР	Description	Status					
		l mple mente d	Not Applicable	M o d I fie d¹	Effective	Unknown	Not Effective
4.7 Procedures for receipt and consideration of public inquiries, concerns, and information submitted regarding local construction activities	Information source and reporting on construction site runoff control measures available to public.		√ 3rd Yr				

a. BMPs

i. General summary

During the second permit year, the City continued implementing the Storm Water Quality Ordinance and enforces its use during all phases of construction. The 2006 Design Standards and Standard Specifications requires in their Improvement Plan Check List, Part V copies of Storm Water Pollution Prevention Plan (SWPPP) and Notice of Intent (NOI) from Contractors/Developers for all projects greater than one acre. A model SWPPP has been prepared to demonstrate to developers and contractors what key information is required when the construction projects are greater than one acre. Every single project is reviewed by both the Community Development Department and the Public Works Department to determine if one acre of land is disturbed in ach project. The following steps are required and enforced in each project than is greater than one acre:

- No construction permit is issued before the SWPPP is approved.
- Routine inspections are conducted on construction sites having open permits. Enforcement per the
 ordinance is executed where required.
- Documentation and tracking of problem sites is performed.
- A priority inspection system has been developed depending upon each site's stage of construction, proximity to Salinas River, previous contractor's performance, repeated neglect of storm water protection systems, etc.

During the second permit year only Miravale II Unit I, a subdivision project, was greater than one acre. The City has enforced all the necessary procedures to prevent pollution from sediments from this project.

ii. Status of Measurable Goals

100% of the first year's measurable goals have been achieved.

iii. Appropriateness

The second permit year's construction site storm water control minimum measures have been appropriate for the permit. When the sewer moratorium was lifted, the storm water ordinance and the model SWPP developed during the first permit year assisted the City to monitor new projects that were ready for construction.

iv. Effectiveness

Determining the effectiveness through the second permit year is difficult to ascertain. The rest of the years of the permiting will provide a greater opportunity to measure the construction control measure's effectiveness in reducing the storm water pollution from the construction sites greater than one acre.

v. Proposed Modifications

There are no modifications proposed.

b. Results

There is no applicable information to be reported this permit year.

Not applicable this year.

c. Summary

Below is a summarization of the storm water activities planned during the next reporting cycle (including an implementation schedule).

The chart below outlines the City's next reporting cycle of storm water activities that will be implemented during the third permit year.

	Dropood	Modif	ied?	Schedule	
BMP	Proposed Measurable Goal	YES	NO	Complete	Ongoing Implementation
	Measurable Coal			this year	
4.1 Regulatory	Complete ordinance			,	Adopted on April 6, 2005
mechanism for	by Dec First Permit			$\sqrt{}$	
controlling polluted	Year				
runoff from	MG: Ordinance				
construction sites.	adopted				

	Dropood	Modif	ied?	Schedule	
BMP	Proposed Measurable Goal	YES	NO	Complete this year	Ongoing Implementation
4.2 Construction site BMPs for controlling erosion & sediment at site	MG: List of acceptable reference materials and resources developed and available to public			√	100% completed. The City Design Standards and Standards Speci fications list the requirements that developments/contractor have to provide with new plans. The City Engineer conducted plan checks on a case-by-case basis. Documents used during the plan- check phases are the existing City Storm Water Ordinance, the California Stormwater Quality Association (CSQA) Construction Handbook, and by checking that plans meet the existing City BMPs
4.3 SWPPP Requirements and Guidelines	Permit Year 1: Model SWPPP developed; NOI & SWPPP required upon adoption of ordinance. MG: 100% sites≥1 acre with SWPPPs			V	100% completed. City Engineer developed model SWPPP based on the existing Storm Ordinance, the existing City BMPs, and the CASQA Construction Handbook' equipments.
4.4 Tracking of sites >1 acre with associated erosion & sediment control measures	Permit Years 1-5: Log of construction sites developed and maintained by City. MG: 100% all construction sites ≥1 acre logged & tracked		√	100% completed City inspectors record construction sites.	On going practice
4.5 Inspections for sediment & erosion control	Permit Year 1: City will develop prioritization criteria and inspection checklist. MG: Prioritization criteria and checklist developed		√	100% completed. Checklist created by City Engineer.	On going practice
4.6 Penalties for non-compliance with runoff control measures	Permit Year 1: Enforcement procedures and tracking to be developed. MG: Enforcement & tracking procedures detailed in writing		V	100% completed City Inspectors enforce Ordinance.	On going practice

	Dronocod	Modif	ied?	Schedule	
ВМР	Proposed Measurable Goal	YES	NO	Complete	Ongoing Implementation
4.7 Procedures for receipt and consideration of public inquiries, concerns, and information submitted regarding local construction activities	•	YES	NO √	Complete this year No.	Ongoing Implementation Implementation will start during the third year of the permit
	number of reports called in documented, follow- up on 100% of reports achieved				

5. Post-Construction Storm Water Management

If your community is subject to Attachment 4 (Supplemental Provisions) of the General Permit, note your compliance with and progress implementing the Design Standards in this section, if applicable.

ВМР	Description	Status					
		Implemented	Not Applicable	Modlfied ¹	Effective	Unknown	Not Effective
5.1 Site design requirements for new development and redevelopment	Limiting the amount of impervious surfaces for new developments reduces the amount of storm water runoff into the City's storm sewer system, thus reducing the amount of sediment and vehicle-generated pollutants entering the system. Requirements for developers to stencil any new catch basins upon construction will reduce the amount of trash and motor oil that would otherwise enter the City's storm sewer system.	√					
5.2 Storage or detention BMPs controlling storm water	Ensuring flows from newly developed or redeveloped areas will be detained before entering storm drainage system to reduce sediment loading into the Salinas River.	√					
5.3 Post-Construction storm water runoff strategies and design standards	Storm water runoff strategies are site-specific, and require analysis on a case-by-case basis. The City defaults to the existing, State-accepted BMPs published in various reference materials to ensure that, as the State requirements for controls are updated, so too are the City's requirements.	√					
5.4 Adopt ordinance, including an enforcement mechanism	To require compliance with implementation of site development controls (as established by the City and outlined in Attachment 4) that prevent or minimize water quality impacts.	√					

ВМР	Description			Status					
		l mple mente d	Not Applicable	M o d I fie d¹	Effective	U n k n o w n	Not Effective		
5.5 Long-term operations and maintenance of BMPs	Procedures in place for staff to conduct inspections and for compliance to be measured and tracked both for implementation of controls and operations and maintenance of those controls. Implementation of this BMP will effectively minimize, and in some cases prevent, erosion and sediment loading into the City's storm sewer system.	√							

a. BMPs

i. General summary

The City of Soledad is subject to Attachment 4 (Supplemental Provisions) of the General Permit. All new development or redevelopment in the City must divert at least 75 percent of the storm water runoff generated by new construction to a detention basin. Currently, one hundred percent of the storm water runoff generated by new constructions is conveyed to detention basins. The existing City Zoning ordinance and the new Storm Water Quality Ordinance have provided the City the necessary tools to require storm water management facilities and long-term maintenance in new developments. These requirements help to capture and convey storm water as appropriate for protecting receiving waters from the impacts of new developments, and are consistent with the categorical design requirements of Attachment 4.

The new 2006 Design Standards and Standard Specifications adopted in June 2006 included storm drain stenciling as a site design requirement in new projects. A copy of the standard design for Drain Markers can be found in Appendix D and is Standard Plan Number 21A.

ii. Status of Measurable Goals

100% of the first year's measurable goals have been achieved.

iii. Appropriateness

Having the post-construction BMPs and the Storm Water Ordinance in place during the first permit year has assisted the City to applied them to each new project during the second permit year reduce storm water pollution to the maximum extent and helped to apply to each new project that was approved.

iv. Effectiveness

Performing construction inspections assures that each BMPs will be installed and maintained during the entire project.

> v. Proposed Modifications

There are no modifications proposed.

b. Results

There is no applicable information to be reported this permit year.

No results are reported during this permit year.

c. Summary

Below is a summarization of the storm water activities planned during the next reporting cycle (including an implementation schedule).

The chart below outlines the City's next reporting cycle of storm water activities that will be implemented during the third permit year.

		Modified?		Schedule	
BMP	Proposed Measurable Goal	YES	NO	Complete	Ongoing
				this year	Implementation
5.1 Site design requirements for new development and redevelopment	Permit Years 2-5: Incorporate storm drain stenciling as a site design requirement beginning Second Permit Year. MG: 100% of new- and re-development sites to have stenciled drainage inlets prior to receiving Notice of Termination		V	Yes	The 2006 City Design Standards added this new requirement for new developments.
5.2 Storage or detention BMPs controlling storm water	MG: 100% of all new- or redevelopment sites will divert min. 75% storm water runoff into detention basin.		V	100% completed	On going practice

		Modif	ied?	Schedule	
BMP	Proposed Measurable Goal		NO	Complete	Ongoing
				this year	Implementation
5.3 Post- Construction storm water runoff strategies and design standards	The City will require developers and planning and development plan review staff to adhere to the requirements of Attachment 4 of the General Permit, beginning in the Second Permit Year. MG: 100% of new- and re-development "priority project" sites will comply with Attachment 4 design standards, and 100% of all other new- and re-development sites will implement Cityapproved post-construction BMPs		V	Yes	On going practice
5.4 Adopt ordinance, including an enforcement mechanism	Complete ordinance by Dec. of First Permit Year MG: Ordinance adopted		√	Adopted on April 6, 2005	
5.5 Long-term operations and maintenance of BMPs	Inspection procedures, database, and log sheet to be developed by end of First Permit Year. Requirements for reporting by developers, homeowners associations, and City maintenance staff to be finalized also by end First Permit Year. MG: Procedures and log developed, reporting requirements developed		1	100% completed	On going practice

6. Pollution Prevention and Good Housekeeping for Municipal Operations

ВМР	Description			Sta	tus		
		Implemented	Not Applicable	Mod Ified ¹	Effective	Unknown	Not Effective
6.1 Street sweeping	Preventing specific pollutants of concern* from entering storm water system *See also BMP 6.11	V					
6.2 Routine cleaning of drainage inlets	Prevent loading of specific pollutants of concern* before leaving the City limits. *See also BMP 6.11	V					
6.3 Guidelines for cleaning of vehicle parts	Established record-keeping of waste basin-unit use	V					
6.4 Used oil disposal	Established record-keeping for used-oil pick up	√					
6.5 Hazardous materials storage	Proper hazardous materials storage	√					
6.6 Hazardous materials training for City employees	Training for liability mitigation and education on ways to reduce the use of hazardous materials in City maintenance activities (for example, other products that may be used to reduce pesticides used for City parks).	√					
6.7 Employee training on storm water management and BMPs	Up-to-date information on storm water management and BMPs. Training for liability mitigation and protection of City's infrastructure system.	V					
6.8 Spill response	Immediate action to contain and cleanup spills	√					

ВМР	BMP Description						
		Implemented	Not Applicable	Modlfied ¹	Effective	Unknown	Not Effective
6.9 Record keeping of spills, leaks, and other discharges at a facility	Tracking of spills, leaks, and other discharges by facility	√					
6.10 Staff Survey	Measure of SWMP effectiveness under current regulations. Objective is to determine known sources of pollution and/or especially problematic/pervasive areas or activities contributing to pollution in storm water, and work toward reducing these sources and activities.		√ 3rd Yr				
6.11 Annual Testing for Pollutants of Concern	Objective is to effectively measure what pollutants are found in distinct areas of the City to better determine what activities may be employed to reduce those specific pollutants from entering the storm drain system in the future.	V					

a. BMPs

i. General summary

During the second permit year, the best management practice that was not completed during the first permit year was completed with the rest of the BMPs. Street sweeping, cleaning of drainage of inlets, proper hazardous waste disposal are regular activities that the Public Works Department perform every year. During the second permit year, the Public Works Department provided its first training on storm water management and BMPs. Videos were purchased and a Public Works Inspector provided the first training class. Hazardous material training classes were arranged for the Public Works Department, the Police Department and the Fire Department. The City of Soledad continues maintaining the implementation of pollution prevention and good housekeeping in its daily operations.

ii. Status of Measurable Goals

100% of the first year's measurable goals have been achieved.

iii. Appropriateness

The current control measures implemented in the City's daily operations appear appropriate in reducing potential storm water pollution. Next year, the appropriateness of the implemented BMPs will be able to be measured when surveys are distributed among the City staff to determine their own opinions on the current BMPs, and how they could be improved.

iv. Effectiveness

The second year of the implementation of the BMPs does not have enough measurable elements to quantify its effectiveness. In the followings years, procedures will be in place to better quantify the effectiveness of the BMPs used.

> v. Proposed Modifications

There are no modifications proposed for this measure at this time.

b. Results

Results of information collected and analyzed are included below.

During the second permit year, two maps were created to illustrate the schedule of the street sweeping areas within the City boundaries. Figures 4 and 5 show the areas and the schedule. The volume collected of street debris is approximately 25 yd³ per week, and approximately 1,200 yd³ of debris is collected per year.

During the cleaning of drainage inlets, approximately 30 yd³ per year of waste was removed from the storm drain system within the City boundaries.

The employee training on storm water management and BMPs started on August 15, 2006. Almost one hundred percent of the Public Work's staff attended this training session. The material used for this training was the video recorded by Santa Ana Regional Water Quality Board named General Construction Storm water Permit compliance Workshop. On September 11, 2006, the Public Works Inspector presented another storm water management training class. Around seventy percent of the Public Works Staff attended this second training. The Storm Water Coordinator attended a Controlling Construction Site Runoff workshop sponsored by the American Public Works Association.

The City developed and coordinated an annual hazardous material training program for the Police, Fire and Public Works Departments, and the first joint hazardous material training class was offered during the Summer of the Second Permit Year.

The City of Soledad conducted their first testing for pollutants. The areas selected are the existing outfalls located within the City limits. Figure 6 shows the location of the sample sites. Some of the outfalls are retention basins and other detention basins. Only six samples were collected out of the seven existing outfalls because one of the outfalls did not have water for the collection. A grab sampling technique was used for the sampling collection. The samples represent only a particular point in time during the storm; therefore, the samples taken do not represent the entire flow. The results for this first testing represent the baseline for the future test comparison, and the results are summarized in Table 3.

None of the results obtained during the first testing are above the maximum contaminant levels set down by the Salinas River Basin Plan, summarized in Table 4 and illustrated at Graph 1 and Graph 2. The high levels of the total and fecal coliform obtained during this first test are indicators that will require further investigation. It is important to note that the high levels of coliform were from one (1) sampling taken during a first flush light rain event. There was some indication of Orthophosphate which could be attributed to fertilizers.

The over use of lawn fertilizers can be reduced through education, and the brochures and articles published in the Soledad Times emphasis the proper use or fertilizers. The Coliform levels can also be reduced by increasing the public awareness regarding the contamination that could be produced when pest's waste ends in the storm drainage system. Many people are unaware of this type of contamination, but if we emphasis the use of plastic bags to pick their pests waste and dispose it properly when they are walking their pets, the message can be transmitted, and the high levels of fecal coliform can be reduced. Cleaning more often the catch basin will also reduces the levels of nitrates, sedimentation and phosphorous. A copy of the sampling lab report can be found in Appendix E.


Table 3: Annual Testing Results

,	gerned de la constitución de la	A CHESTING	edicipliside capitales of the control of the contro	The Control of the Co	Peter Park Property Control Property Con	ont.	
		Ation Re Told Miles	dialist of Call	are Mesar glare	edicional de	A recorded to the special spec	Caffer and
	Street :3	edestreet Site	ete Grade Of Ade	st Dr. Date . S.	eter Sate	the Date (Elge of Long A
. spet	ig Atari	Matrial Ago, 2°	it alocal servicing	greate not creat	Parion Son	istigary Sover	tar of St
<u> </u>	Outrato C	Outrait of	Outland at it	Outratore's C	Out of Astroi	one on the col	Job Sutfall Marke C
Ammonia (N)				•			<i>,</i>
mg/l	0.09	0.51	Pond dried, no collection done	0.17	0.22	0.18	0.2
Coliform Fecal			Pond dried, no				
#/100 ml	1400	130	collection done	1700	2200	900	5000
Coliform Total #/100 ml	9000	>=16000	Pond dried, no collection done	>=16000	>=16000	>=16000	>=16000
Conductivity	9000	>=16000		>=16000	>=16000	>=16000	>=16000
umho/cm	130	70	Pond dried, no collection done	116	130	100	116
Copper (Cu)			Pond dried, no				
ug/L	ND	ND	collection done	ND	ND	ND	ND
Lead (Pb)			Pond dried, no				
ug/L	ND	12	collection done	8	ND	ND	ND
MBAS surfactants	0.26	ND	Pond dried, no	ND	0.05	ND	0.42
mg/l NO3	0.26	ND	collection done	IND	0.05	ND	0.12
mg/L	1	1	Pond dried, no collection done	2	87	2	ND
Oil & Grease							
mg/L Ortnophospnate	1	2.6	Pond dried, no collection done	1.3	2.9	3.7	3
(P)			Pond dried, no				
mg/l	0.11	0.14	collection done	0.25	0.31	0.17	0.15
PH	7.0	7.4	Pond dried, no	7.5	7.4	7.0	7.7
Std Units Total Kjeldahl	7.8	7.4	collection done	7.5	7.4	7.6	7.7
Nitrogen			Pond dried, no				
ug/L	ND	1.6	collection done	ND	1.6	1.4	ND
Total Organic Carbon			Pond dried, no				
mg/L	6.7	8	collection done	6.4	14	12	13
	No tested,	No tested,	December 1				
Total Phenol	incorrect sample container	incorrect sample container	Pond dried, no collection done	ND	ND	ND	ND
Total Suspended Solids							
mg/l	7	327	Pond dried, no collection done	85	58	143	26
Turbidity			Pond dried, no				
NTU	18	350	collection done	200	85	200	70
Zinc			Pond dried, no				
ug/L	ND	188	collection done	144	63	101	ND
(DO)	40.5		Pond dried, no	40.4	0.7	40	40.0
mg/L	10.5	9	collection done	10.4	9.7	10	10.2


Table #4 Median Ground Water Objectives per Salinas Basin Plan

Salinas River Lower Forebay Sub-basin								
Tested	Objective	Ave. Results						
TDS	1500	55.2						
CI	250	5						
SO4	850	2						
В	0.5	0.02						
Na	150	15.5						
Nitrogen								
as N	8	0.77						
Toxic Metals (Concentration							
Tested	Objective							
Cadmium	30	0.5						
Chromium	50	0.5						
Copper	30	0.5						
Lead	30	3.3						
Mercury	0.2	0.01						
Nickel	400	0.5						
Zinc	200	82.7						

Graph 1: Median Ground Water Objectives per Salinas Basin Plan – Chart#1



December 2006



Graph 2: Median Ground Water Objectives per Salinas Basin Plan – Chart #2

The basin objectives for all inland surface water, enclosed bays and statuaries are listed in the General Objectives II.A.2 of Chapter 3. Water Quality Objectives and below is the list of the general objectives.

Color

Waters shall be free of coloration that causes nuisance or adversely affects beneficial uses. Coloration attributable to materials of waste origin shall not be greater than 15 units or 10 percent above natural background color, whichever is greater.

Tastes and Odors

Waters shall not contain taste or odor-producing substances in concentrations that impart undesirable tastes or odors to fish flesh or other edible products of aquatic origin, that cause nuisance, or that adversely affect beneficial uses.

Floating Material

Waters shall not contain floating material, including solids, liquids, foams, and scum, in concentrations that cause nuisance or adversely affect beneficial uses.

Suspended Material

Waters shall not contain suspended material in concentrations that cause nuisance or adversely affect beneficial uses.

Settleable Material

Waters shall not contain settleable material in concentrations that result in deposition of material that causes nuisance or adversely affects beneficial uses.

Oil and Grease

Waters shall not contain oils, greases, waxes, or other similar materials in concentrations that result in a visible film or coating on the surface of the water or on objects in the water, that cause nuisance, or that otherwise adversely affect beneficial uses.

Biostimulatory Substances

Waters shall not contain biostimulatory substances in concentrations that promote aquatic growths to the extent that such growths cause nuisance or adversely affect beneficial uses. Sediment

The suspended sediment load and suspended sediment discharge rate of surface waters shall not be altered in such a manner as to cause nuisance or adversely affect beneficial uses.

Turbidity

Waters shall be free of changes in turbidity that cause nuisance or adversely affect beneficial uses.

Increase in turbidity attributable to controllable water quality factors shall not exceed the following limits:

- 1- Where natural turbidity is between 0 and 50 Jackson Turbidity Units (JTU), increases shall not exceed 20 percent.
- 2.- Where natural turbidity is between 50 and 100 JTU, increases shall not exceed 10 JTU.
- 3- Where natural turbidity is greater than 100 JTU, increases shall not exceed 10 percent.

Allowable zones of dilution within which higher concentrations will be tolerated will be defined for each discharge in discharge permits.

pH

For waters not mentioned by a specific beneficial use, the pH value shall not be depressed below 7.0 or raised above 8.5.

Dissolved Oxygen

For waters not mentioned by a specific beneficial use, dissolved oxygen concentration shall not be reduced below 5.0 mg/l at any time. Median values should not fall below 85 percent saturation as a result of controllable water quality conditions.

Temperature

Temperature objectives for Enclosed Bays and Estuaries are as specified in the "Water Quality Control Plan for Control of Temperature in the Coastal and Interstate Waters and Enclosed Bays and Estuaries of California" including any revisions thereto.

Natural receiving water temperature of intrastate waters shall not be altered unless it can be demonstrated to the satisfaction of the Regional Board that such alteration in temperature does not adversely affect beneficial uses.

Toxicity

All waters shall be maintained free of toxic substances in concentrations which are toxic to, or which produce detrimental physiological responses in, human, plant, animal, or aquatic life. Compliance with this objective will be determined by use of indicator organisms, analyses of species diversity, population density, growth anomalies, toxicity bioassays of appropriate duration, or other appropriate methods as specified by the Regional Board. Survival of aquatic life in surface waters subjected to a waste discharge or other controllable water quality conditions, shall not be less than that for the same water body in areas unaffected by the waste discharge or, when necessary, for other control water that is consistent with the requirements for "experimental water" as described in Standard Methods for the Examination of Water and Wastewater, latest edition. As a minimum, compliance with this objective shall be evaluated with a 96-hour bioassay.

In addition, effluent limits based upon acute bioassays of effluents will be prescribed where appropriate, additional numerical receiving water objectives for specific toxicants will be established as sufficient data become available, and source control of toxic substances is encouraged.

The discharge of wastes shall not cause concentrations of unionized ammonia (NH3) to exceed 0.025 mg/l (as N) in receiving waters.

Waters shall not contain organic substances in concentrations greater than the following: Methylene Blue

Activated Substances

0.2 mg/l

Phenols

0.1 mg/l

PCB's 0.3 mg/l

Phthalate Esters 0.002 mg/l

Radioactivity

Radionuclides shall not be present in concentrations that are deleterious to human, plant, animal, or aquatic life; or result in the accumulation of radionuclides in the food web to an extent which presents a hazard to human, plant, animal, or aquatic life.

COLD FRESHWATER HABITAT (COLD)

pH

The pH value shall not be depressed below 7.0 or raised above 8.5. Changes in normal ambient pH levels shall not exceed 0.5 in fresh waters.

Dissolved Oxygen

The dissolved oxygen concentration shall not be reduced below 7.0 mg/l at any time.

Temperature

At no time or place shall the temperature be increased by more than 5oF above natural

receiving water temperature.

Chemical Constituents

Waters shall not contain concentrations of chemical constituents known to be deleterious to fish or wildlife in excess of the limits listed in Table 3-5.


FISH SPAWNING (SPWN)


Cadmium


Cadmium shall not exceed .003 mg/l in hard water or .0004 mg/l in soft water at any time. (Hard water is defined as water exceeding 100 mg/l CaCO3.)

Dissolved Oxygen

The dissolved oxygen concentration shall not be reduced below 7.0 mg/l at any time.







c. Summary

Briefly summarize the storm water activities you plan to undertake during the next reporting cycle (including an implementation schedule). If you propose activities that differ from those originally proposed in the approved SWMP, provide justification.

The following chart outlines the City's activities that will be implemented within the Pollution Prevention Housekeeping for Municipal Operations.

	Dropood Messurable	Modified?		Schedule			
BMP	Proposed Measurable Goal	YES	NO	Complete this year	Ongoing Implementation		
6.1 Street sweeping	MG: Schedule prepared, volume of removed materials documented		1	100% completed	On going practice		
6.2 Routine cleaning of drainage inlets	Permit Year 1: City will have a log of each inlet in storm drainage system with cleaning tallies beginning Fall of First Permit Year MG: 100% inlets logged		√ 	100% completed	On going practice		
6.3 Guidelines for cleaning of vehicle parts	Permit Year 1: City will develop log by Summer First Permit Year. MG: Log developed		V	100% completed	On going practice		
6.4 Used oil disposal	Permit Year 1: City will develop log by Summer First Permit Year MG: Log developed		1	100% completed	On going practice		
6.5 Hazardous materials storage	MG: 100% hazardous materials stored in proper facility and per proper guidelines		√ √	100% completed.	On going practice		
6.6 Hazardous materials training for City employees	Permit Years 1-5: City will have sign-up sheet for staff at each PW safety training by Winter of First Permit Year MG: 75% PW Staff attending min. 12 Haz mat trainings/yr		√	100% completed. The Public Works Department, the Police Department and Fire Department had their first joint Haz mat training class during the summer of the second permit year.	On going practice		
6.7 Employee training on storm water management and BMPs	Permit Year 2: First training session held at PW staff meeting addressing new information taught to Inspector by Summer Second Permit Year MG: Training session held; 50% PW staff in attendance for training session.		V	100% completed The e training was held on August 15, 2006 and September 11, 2006.	On going practice		
6.8 Spill response	MG: 100% spills responded to		1	100% completed	On going practice		

	Proposed Measurable	Modif	ied?	Schedule	
BMP	Goal		NO	Complete this year	Ongoing
	Goal				Implementation
6.9 Record keeping of spills,	MG: 100% occurrences documented		√	100% completed. The City currently logs the invoices of the companies that	On going practice
leaks, and other discharges at a facility				perform the cleanup. More formalized documentation is being developed.	
6.10 Staff Survey	Questionnaire will be distributed by June 30 and collected by July 15 (each year) beginning in Third Permit Year. SWMP reporting to RWQCB in September each year will incorporate findings. MG: 75% of City PW staff to provide feedback; plan to address feedback developed and incorporated into the SWMP.		√	No.	Implementation will start during the third year of the permit
6.11 Annual Testing for Pollutants of Concern	Testing to begin in First Permit Year MG: Volume pollutants prevented from leaving City limits calculated; reduction in pollutant levels present in samples determined, plans for applying data to SWMP activities developed.		V	100% completed	On going practice

Section 4. Certification

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

Signature of Permittee (legally responsible person)

n W. Price

Date Signed

Clifton W. Price

Public Works Director

APPENDIX A

Brochures English & Spanish - Examples

English **B**rochure

Stop Storm Water Runoff Pollution!



Help Our Community, Stop Storm Water Runoff Pollution!

City of Soledad 246 Main Street Soledad, CA 93960 Phone (831) 678-3963 Fax (831) 679-3965 http://www.cityotsoledad.com

To REPORT CLOSGED CATCH BASINS, CALL: Dity of Sciedad Public Works Department (831) 678-3963 between 8:00 A M to 5:00 P M After 6:00 P M. call (831) 678-3963 entersion 121

TO REPORT ILLEGAL DUMPING CALL: City of Soledad Public Works Department at (831) 676-3963 between 8.00 A.M to 5.00 P.M. After 5.00 P.M. cell (831) 676-3963 extension 121

TO RECYCLE USED MOTOR OIL CALL:

TO DISPOSE OF HOUSEHOLD HAZARDOUS WASTE CALL Johnson HHW Colection Facility, Salmas Valley Sold Wileste Authority Figenesis at (831) 6787-9485 Sun Street HHW Facility, Salmas Valley, Sold Vallet Authority Disposel at (831) 424-6500

The City of Soledad is counting on you!

The City of Soledad Storm Water Management Plan






Protect the Environment, Stop Storm Water Pollution!

Help our community

WHAT IS THE OBJECTIVE?



The objective of the SWMP is to protect the storm water quality by limiting the entrance of pollutants into the City of Soledad storm water system.

WHAT IS RUNOFF?

Runoff is water from rain, agricultural or landscape irrigation, or from other sources that flows over the paved surface.

WHAT IS STORM WATER POLLUTION?

When the storm water runoff flows over impervious surfaces; such as pavements, roofs, compacted soils and rock outcrops; it can collect debris, chemicals, dirt, and other pollutants. For example, automobile oil, grease and debris can be carried by storm water runoff into any water body causing pollution and adverse effects on plants, fish, animals and people.

WHAT IS A NONPOINT SOURCE POLLUTANT?

Nonpoint source pollutants are pollutants that cannot be traced to a single pipe, or single point of source.

IS STORM WATER TREATED?

The storm water that is collected and transported in the storm drain system flows directly to the river or ocean without any treatment. The final destination of any pollutant that is illegally discharged into the storm drain system is our rivers and oceans!

REDUCING STORM WATER RUNOFF IN OUR COMMUNITY

You can prevent pollution by doing some of the following household and automobile activities:

HOUSEHOLD & HOME ACTIVITIES

- Never discharge anything down the storm drain system.
- Sweep paved areas to keep waste away from the storm water system. Do not use water to clean your sidewalks or driveways.
- 3) Clean up your pet waste
- 4) Buy less toxic household products.
- Store all toxic products and use them properly.
- Filter and reuse paint thinner or brush cleaners.
- Take unwanted paints, cleaners and chemicals to an approved Household Hazardous Waste Facility.

PERSONAL AUTOMOTIVE CARE

- 1) Recycle used motor oil and antifreeze.
- Inspect and maintain your car to reduce leakage of oil, antifreeze and other
 fluids
- Use a commercial car wash that treats or recycles its wastewater, or wash your car on your yard so the water infiltrates into the ground.



PET CARE ACTIVITIES THAT PREVENT STORM WATER POLLUTION.



- Carry a pooper-scooper or plastic bag with you to pick up your pet's waste when walking your dog. Pet's waste can be washed up into the storm drain system.
- Dispose pet waste by flushing it down the toilet or placing it in the trash.

Spanish Brochure

¡Pare el Derrame de Agua Contaminada a las Alcantarillas de Tormenta! ■



Ayude a Nuestra
Comunidad, Pare el
Derrame de Agua
Contaminada a las
Alcantarillas de
Tormenta!

Plan De Gerencia De Alcantarillas de Tormenta De La Ciudad De Soledad ■



248 Main Street Soledad, CA 93960 Phone (831) 678-3963 Fax (831) 679-3965 http://www.cilyofsoledad.com

City of Soledad

PARA REPORTAR OBSTRUCCIONES EN LAS PALANGANAS, LAME AL: Departamento de Coras Publicas de la Cludad de Soledad (831) 678-3963 entre 8:00 A.M. a. 5:00 P.M. Después de las 5:00 P.M. lame al (831) 678-3983 extensión 121

PARA REPORTAR DESECHO ILEGAL LLAME AL: Departamento de Coinse Publicas de la Cluidad de Soledad (831) 673-3993 entre 8:00 A M a 5:00 P M. Después de las 5:00 PM llame al (831) 678-3963 extension 121

PARA RECICLAR ACEITE USADO DE MOTOR LLAME AL: Servicio de Recicleje y Desechos Tri-Cities al (888) 678-6798

PARA DESECHAR DESPERDICIOS PELIGROSOS LLAME A: Johnson HHW Collection Facility. Salinas Valley Solid Weste Authority Disposal at (831) 675-2143. Sun Street HHW Facility. Salinas Valley Solid Weste Authority Disposal at (831) 424-5520.



Ayude a nuestra comunidad

¡La Ciudad de Soledad cuenta con usted! ¡Proteja el ambiente, Pare la contaminación!

CUAL ES EL OBJECTIVO?

La Ciudad de Soledad desarrollo y adopto el Plan de Gerencia de Alcantarillas de Tormenta (SWMP) en el 2004.

El objetivo del SWMP es de proteger la calidad de agua a las alcantarillas de tormenta limitado la entrada de contaminación al sistema de alcantarillas de la Ciudad de Soledad.

¿QUE ES DERRAME DE AGUA?

El derrame de agua es causado por la lluvia, agricultura o irrigación del jardín, o de otras fuentes que fluyen sobre las superfícies en pavimentadas.

¿QUE ES LA CONTAMINACIÓN DE AGUA DE TORMENTA?

Cuando el agua fluye sobre superficies impermeables; por ejemplo los pavimentos, techos, los suelos condensados y los altoramientos de roca, la corriente puede recoger los escombros, productos químicos, suciedad, y otros contaminantes. Por ejemplo, el aceite de automóvil, la grasa y escombros se pueden derramar en el agua y se van a cualquier cuerpo de agua causando contaminación y efectos adversos a las plantas, los pescados, los animales y la gente.

¿QUE ES UN CONTAMINANTE SIN PUNTO DE ORIGEN?

Un contaminante sin punto de origen es un contaminante que no puede ser localizado en una sola pipa, o un solo lugar de origen.

¿ES TRATADA EL AGUA DE TORMENTA?

El agua de tormenta es colectada y transportada en el sistema de drenaje de tormenta o alcantarillas que fluye directamente a info u océano son inigún tratamiento. El destino final de cualquier contaminante que es desechado ilegalmente en el sistema de alcantarilas de tormenta termina en nuestros ríos y océanos!

REDUCIENDO EL DERRAME DE AGUA DE TORMENTA EN NUESTRA COMUNIDAD

Usted puede prevenir la contaminación haciendo lo siguiente con sus actividades en la casa y con su automóvil:

ACTIVIDADES DE CASA

- Nunca deseche cualquier cosa dentro del sistema de alcantarilla de tormenta.
- Barra las áreas para mantener los escombros alejados del sistema de alcantarilla. No utilice el agua para limpiar las aceras y caminos de entrada.
- Limpie el excremento de su mascota.
- Compre menos productos tóxicos para la
- Almacene todos los productos tóxicos y úselos apropiadamente.
- Filtre y use de nuevo el "thinner" de pintura o limpiadores de brochas.
- Lleve las pinturas, los limpiadores y los productos químicos indeseados a una facilidad aprobada para desechos peligrosos de la casa.

CUIDADO DE SU AUTO PERSONAL

- Recicle el aceite de motor y anticongelante usado.
- Examine y mantenga su carro para reducir la salida de aceite, anticongelante y de otros líquidos.
- Para lavar su carro utilice jabón comercial que trate o recicle las aguas residuales, o lave su carro en su yarda para que el agua se infiltre en la tierra.



CUIDADO DE MASCOTAS QUE PREVIENE LA CONTAMINACIÓN DEL AGUA DE TORMENTA



-) Lleve un recogedor o una bolsa de plástico con usted para recoger los excrementos de su perro al caminar. Los excrementos de su mascota pueden irse entre el agua al sistema de tormenta en las alcantarillas.
- Deseche los excrementos de su mascota en el inodoro o en la basura

APPENDIX B

Soledad Times Articles – Examples (English & Spanish)

Article I (English & Spanish)



CITY OF SOLEDAD

STORMWATER PROTECTION STARTS WITH YOU



HELP OUR COMMUNITY



DON'T POUR FLUIDS INTO YOUR SEPTIC SYSTEM, SANITARY SEWER, DRY WELL, ON THE GROUND, STORM DRAIN INLETS, OR IN THE TRASH



USE A BROOM RATHER THAN A HOSE TO CLEAN UP GARDEN CLIPPINGS, DIRT AND LITTER FROM SIDEWALKS, PATIOS AND DRIVEWAY.



CONSERVE WATER AND REDUCE THE AMOUNT OF RUNOFF BY NOT OVER WATERING YOUR LAWN AND GARDEN.



KEEP UP CAR MAINTENANCE TO REDUCE LEAKAGE OF OIL, ANTI FREEZE AND OTHER FLUIDS.



WHEN CHANGING CAR FLUIDS, USE A DRIP PAN TO COLLECT ANY SPILLS. IF A SPILL OCCURS, SOAK IT UP USING AN ABSORBENT MATERIAL SUCH AS KITTY LITTER OR SAWDUST



To REPORT CLOGGED CATCH BASINS, CALL: City of Soledad Public Works Department (831) 678-3963

TO REPORT ILLEGAL DUMPING CALL: nent at (831) 678-3963 between 8:00 A.M to 5:00 P.M. and (831)755-5111 for other hours

TO RECYCLED USED MOTOR OIL CALL: Tri-Cities Disposal and Recycle Service at (888) 678-6798

TO DISPOSE HOUSEHOLD HAZARDOUS WASTE CALL: on Landfill. Salinas Valley Solid Waste Authority Disposal at (831) 675-2165

AOOUJOOQUESS

COMIENZA CIUDAD DE SOLEDAD LA PROTEGGIÓN DE LAS ALGANTO COMIENZA O



NO ECHE LÍQUIDOS EN SU SISTEMA SÉPTICO, DRENAJE DE SANITARIO, POZO SECO, LA TIERRA, ALCANTARILLAS, O EN LA BASURA.



UTILICE UNA ESCOBA EN LUGAR DE UNA MANGUERA PARA LIMPIAR RECORTES DE JARDÍN. TIERRA Y BASURA DE LAS AGERAS, PATIOS Y CAMINO DE ENTRADA.



CONSERVE AGUA Y REDUZCA LA CANTIDAD DE AGUA DESPERDICIADA, NO SOBRE RIEGUE SU CÉSPED Y JARDÍN.




CONTINUÉ EL MANTENIMIENTO DE SU COCHE PAR REDUCIR EL GOTEO DE ACEITE, ANTI-CONGELANTE Y OTRO LÍQUIDOS.



CUANDO CAMBIE LOS LÍQUIDOS DE SU COCHE, UTILICE UNA CACEROLA PARA RECOGER CUALQUIER DERRAME. SI DOURRE, RECOJA EL LIQUIDO CON UN MATERIAL ABSORBENTE TAL COMO ASERRÍN Y DESÉCHELO APROPIADAMENTE.







PARA DESECHAR DESPERDICIOS PELIGROSOS LLAME A: Johnson Canyon Landfill, Salinas Valley Solid Waste Authority Disposal al (831) 675-2165

December 2006 54

Article **2** (**E**nglish & **S**panish)



Help our community,

Stop Stormwater Pollution!

You can help us by doing the following:



Store engines, transmissions, and other oil parts inside proper containers, keep them away from the rain



Never place battery acid on the ground or into a storm drain



Inspect your car for leaks, and recycle motor oil



Sweep up driveways and side-walks, do not use water



Use fertilizers and pesticides sparingly. Avoid application if the forecast calls for rain.



Wash your car at the car wash instead of washing it in the driveway



When doing outdoor projects, protect the storm drains from debris and other materials.

Te REPORT CLOGGED CATCH BASINS, CALL:
City of Soledad Public Works Department (631) 678-3963 between 5:00 A.M. to 5:00 P.M.
After 5:00 P.M. call (831) 678-3963 extension 121 TO REPORT ILLEGAL DUMPING CALL:
City of Soledad Public Works Department at (831) 678-3963 between 8:00 A M to 9:00 P M.
After 5:00 P M. cell (837) 678-3963 actinsion 121 TO RECYCLED USED MOTOR OIL CALL: Tri-Oties Disposal and Recycle Service at (888) 578-5798

TO DISPOSE HOUSEHOLD HAZARDOUS WASTE CALL: Johnson Canyon Landill, Salinas Valley Solid Vaste Authority Disposal at (831) 675-2165 The City of Soledad is counting on you!



¡No Contamine las Alcantarillas!

Usted puede ayudarnos haciendo lo siguiente



Almacene los motores, transmisiones y otras piezas de aceite dentro de los envases apropiados, mantengalos fuera de la



Nunca coloque el ácido de batería en la tierra o en los drenajes



Examine su coche para saber si gotea, y recicle el aceite de



Barra la entrada de su cochera y las aceras, no use el agua



Utilice los fertilizantes y los pesticidas escasamente. Evite usarlos si se pronostica Iluvia



Lave su coche en el auto lavado en vez de lavarlo en la entrada de la cochera



Cuando haga proyectos al aire libre, proteja el drenaje de basura y otros materiales

PARA REPORTAR OBSTRUCCIONES EN DREMAJES, LLAME AL:
Departamento de Obras Publicas de la Cudad de Soledad (931) 978-3993 entre las 8 0.00 A.M a las 5:00 P.M
Despartamento de Las 5:00 P.M inme al (301) 678-3993 automoto 123 PARA REPORTAR DESECHO ILEGAL LLAME AL:

e Otras Pobitas de la Ciudad de Soledad (831) 678-3963 entre las 8:00 A M a las 5:00 P M
Después de las 5:00 PM liame al (831) 678-3983 extensión 121 PARA RECICLAR ACEITE USADO DE MOTOR LLAME AL: Sensolo de Recislaje y Desechos Tri-Cities al (886) 676-6796 PARA DESECHAR DESPERDICIOS PELIGROSOS LLAME A: n Canyon Landfil, Sainas Valley Sold Waste Authority Disposal of (93)

La Ciudad de Soledad, iestá contando con usted!

December 2006 55

$m{A}$ rtıcle $m{3}$ ($m{E}$ nglish & $m{S}$ panish)





APPENDIX C

Soledad Outfalls



Outfall Number I Retention Pond along Gabilan Street

Area is cleaned and maintain by the City.

No major structure damage was noticed. Sediments, debris and high weeds around the outfall area were found during the inspection. The Public Works Department maintains the outfall area periodically.

This outfall is located at a retention pond along Gabilan Street. The retention pond receives the water from the subdivision of Miravale I, Phase I, II and III that are located to the northeast of Toledo Street to the east side of Orchard Lane and from Gabilan Drive to the north end of the City, and this outfall will be receiving the runoff from the new subdivision Miravale II, Unit I. This retention pond is not connected to the rest of the City storm water system, and the storm water that enters the retention pond stays in this retention pond. The City plans to connect these storm drainage systems from these subdivisions to the rest of the City's storm water system when the storm water drainage

system's capacity along Gabilan Drive and San Vicente Road will be retrofitted by increasing the sizes of the pipes.

Outfall Number 2 Detention Pond at Santana Park

The outfall Number 2 is located at Santana Park. The outfall structure did not show any structural damage, sediments inside the outfall were found during the inspection. The Public Works Department maintains the outfall area periodically.



converge at the intersection of West and Front Street. of the Soledad Waste Water Treatment Plant.



This outfall is a detention pond that receives the storm water runoff from the subdivision located between the westside of Toledo to Barcelona Street from Gabilan Drive to Portola Drive. After the detention pond excesses the maximum capacity, this runoff is transported from Gabilan Drive to the intersection of Front and West Street Street. Runoffs from Andalucia Drive, North Street, Main and West Street also

converge at the intersection of West and Front Street. The final travel path of the storm water runoff ends at outfall

Outfall Number 3 Detention Pond at Veterans Memorial Park



Outfall number 3 is located at the detention pond at the Veterans Memorial park.

Structure was not damaged and no sediments or debris were found inside or outside the structure.

The Public Works Department maintains the outfall area periodically.

This detention pond receives storm water runoff from subdivisions located at Entrada Drive, Vista de Soledad, Gabilan Drive and San Vicente Road. The water is detained and then release to the San Vicente drainage system when the capacity of the basin is reached.

Outfall Number 4 Retention Pond along Front & Highway 101

The outfall at the retention pond located along Front Street & Highway 101 had debris around the area. Structure did not present any damage during the inspection. The Public Works Department maintains the outfall area periodically.

This retention pond is located along Front



Street. The storm water that enters this retention pond stays inside the pond. The drainage system in Front Street collects the runoff from the south side of Front Street flowing west from Oak Avenue, flowing south of Monterey and Market Street, west of Oak Avenue to the intersection at Front Street and West Street.



Outfall Number 5 Outfall at Treatment Plant

The main City's outfall did not show any structural damage, debris and plastic bottles were found at site. The Public Works Department maintains the outfall area periodically.

The City's outfall receives the runoff from the entire City except from the retention pond located along Gabilan Drive and the retention pond of Front Street.

The runoff is discharged to the river.

Outfall Number 6



No structural damaged was noticed, weed removal was recommended to maintain the area.

This outfall receives the runoff from Monterey Street, First and Third Street, and Pine Street. The runoff is discharged into a culver that crosses under Highway 101.

Outfall Number 7 Detention Basin at Market Street & San Vicente



Detention Pond area is located at the intersection of Market Street and San Vicente. No structural damage was noticed.

The detention Pond receives the runoff from the Subdivision located between the west side of West Street to San Vicente Road and from Market Street to Viejo Gabriel, when the capacity is reached the water is released to the storm drainage system located along San Vicente Road. The detention pond will be eliminated when the capacity of the system along San Vicente Road will be increased.

APPENDIX D

Storm Drain Markers

PART II STANDARD PLANS

NO). THE	MO	. THE
1.	Curbs and Gutters	27.	Requirements Prior to Public
1A.	Paving Requirements Adjacent to	•	Works Acceptance Inspection
	New Curb & Gutter	28.	
1B.	Cross Gutters	29.	Time Requirements for Air
2.	Sidewalks	29.	Test of Sanitary Sewer
3⋅	Street Structural Sections	30.	
4.	Access Ramps	31.	Flushing Inlet Frame and
5⋅	Residential Drive Approach		Cover
5A.	2/3 Car Garage Driveway Approach	32.	Flushing Inlet
5B.	Commercial Drive Approach	33.	Sewer Lateral
6.	Driveway Approach for Roll-	34.	Percolation Pond Detail
	Type Curb	35.	Percolation Pond Designs
7.	Alley Approach and Section	36.	Blank
8.	Tree Well	37.	Street Name Signs
9.	Side Yard Detail	38.	Traffic Signs (Stop-Yield)
10.	City Monument	39.	Raised Pavement Markers
11.	Trench Safety Requirements		and Striping
12.	Blank	40.	Pavement Markings
13.	Trench Backfill and Surface Restoration	41.	Parking Standards
14.	Misc. Storm Drain Details	42.	Chain Link Fence
15.	Curb Drain	43.	Masonry Non-Access Wall
16.	Type "A" Catch Basin (36")	44.	Wooden Barricade
17.	Type "B" Catch Basin (24")	45.	Wooden Perimeter/Property Line
18.	Type "C" Catch Basin (36")	_	Fence
19.	Type "D" Side Opening Catch Basin	46.	Street Tree Planting
20.	Type "E" Top Opening Catch Basin	47.	Slope Grading
21.	Type "F" R.C.P Catch Basin	48.	Utility Service Pedestal
₹ 21A.	Storm Drain Markers	49.	P.C.C. Lighting Foundation
22.	Manhole Frame and Cover	50.	Lighting Poles
23.	Manhole Frame and Cover	51.	Utility Locations (Typical)
0.1	Adjustment	52 .	Typical Lot Grading
24.	Manholes – Type "A" and "B"	53.	Mail Box Cluster
	Manhole – Type "C"	54.	Site Security, Clean-up & Erosion
26.	Cast-In-Place Concrete Pipe		Control
		55.	Public Works Inspection Checklist



Part: ORD

OBTAIN THE ABOVE STORM DRAIN MARKER FROM:

DAS MANUFACTURING, INC.

3610 CINNAMON TRACE DRIVE

VALRICO, FL 33594

800-549-6024 FAX 831-681-5807

E-MAIL: SALES@CURBMARKER.COM

- STORM DRAIN MARKER TO BE USED ON CITY CATCH BASINS
 OR OTHER AS APPROVED BY THE DIRECTOR OF PUBLIC WORKS.
- 2. APPLY TO CATCH BASIN AT TOP OF CURB, CENTERED.
- 3. APPLY TO SURFACE WHICH IS FLAT, DRY AND FREE OF ANY LOOSE DEBRIS.
- ONLY USE MANUFACTURER'S ADHESIVE, ASSURING PROPER COVERAGE PRIOR TO APPLICATION.

DEPARTMENT OF PUBLIC WORKS

CITY OF SORDERSON

STANDARD PLAN

No. 42180

EXP. 23100

CKED BY:

WALTER A. GRANT, CITY ENGINEER - R.E. 42180 EXP. 28-05

APPENDIX E

Test Results



City of Soledad P.O. Box 156 Soledad, CA 93960 Waste Water District **Attn: Clifton Price**

MONTEREY COUNTY HEALTH DEPARTMENT

Consolidated Chemistry Laboratory

1270 Natividad Road Salinas, CA 93906 Phone (831)755-4516 (831) 755-4652

Natividad Road S. (83.) 755-4516 Page (83.) 83. (83.) ELAP Certification Number 3395

Page 1 of 5

Monday, May 01, 2006

Lab Number:

AA86883

Sample Site:

WASTEWATER SIDE

Source Code: Sample ID:

Sample Comments:

Routine Storm Water. Dissolved Oxygen 9.7 mg/L.

Client Code: SOLEDA-W Collection Date/Time: 3/14/2006 7:40 Submittal Date/Time: 3/14/2006 12:39 Sample Collector: ROMERO G

Analyte	Method	Unit	Result	PQL	Date Analyzed
Ammonia(N)	EPA350.3	mg/l	0.22	0.05	3/17/2006
Coliform; Fecal	SM9221E	#/100 ml	2200	Variable	3/14/2006
Coliform; Total	SM9221B	#/100 ml	>=16000	Variable	3/14/2006
Conductivity	EPA120.1	umho/cm	130	N. (. 1. V.)	3/14/2006
Copper (Cu)	EPA200.8	ug/L	ND	0.5	3/21/2006
Lead (Pb)	EPA200.8	ug/L	ND	0.5	3/21/2006
MBAS surfactants	Subcontract	Attached	Completed	Attached	3/15/2006
NO3 (Nitrate)	EPA300	mg/L	2	4	3/14/2006
Oil & Grease	Subcontract	Attached	Completed	5 5	3/26/2006
Orthophosphate as P	EPA365.2	mg/l	0.31	0.03	3/15/2006
pH (Laboratory)	EPA150.1	Std Units	7.4	N/A	3/14/2006
Total Kjeldahl Nitrogen	Attached	Attached	Completed	Attached	3/21/2006
Total Organic Carbon	Attached	Attached	Completed	Attached	3/20/2006
Total Phenol	Attached	Attached	Completed	Attached	3/24/2006
Total Suspended Solids	EPA160.2	mg/l	58	5	3/16/2006
Turbidity (Laboratory)	SM2130-B	NTU	85	0.05	3/14/2006
Zinc (Zn)	EPA200.8	ug/L	63	5	3/21/2006

mg/L: Milligrams per liter (=ppm) PQL: Practical Quantitation Limit

DLR: Detection Limit for Reporting

ug/L: Micrograms per liter (=ppb) MCL: Maximum Contaminant Level

*: Primary Standards **: Secondary Standards

ND: Not Detected

N/A: Not Applicable

*** : Action Level

AA86884 Lab Number:

Sample Site:

FRONT ST AT NESTLES

Source Code: Sample ID:

Collection Date/Time: Submittal Date/Time:

Client Code:

SOLEDA-W 3/14/2006

8:05 3/14/2006 12:39

Sample Collector:

ROMERO G

Sample Comments:

Routine Storm Water. Dissolved Oxygen 10.0 mg/L.

Analyte	Method	Unit	Result	PQL	Date Analyzed
Ammonia(N)	EPA350.3	mg/l	0.18	0.05	3/17/2006
Coliform; Fecal	SM9221E	#/100 ml	900	Variable	3/14/2006
Coliform; Total	SM9221B	#/100 ml	>=16000	Variable	3/14/2006
Conductivity	EPA120.1	umho/cm	100	1	3/14/2006
Copper (Cu)	EPA200.8	ug/L	ND	0.5	3/21/2006
Lead (Pb)	EPA200.8	ug/L	ND	0.5	3/21/2006
MBAS surfactants	Subcontract	Attached	Completed	Attached	3/15/2006
NO3 (Nitrate)	EPA300	mg/L	2	1	3/14/2006
Oil & Grease	Subcontract	Attached	Completed	5	3/26/2006
Orthophosphate as P	EPA365.2	mg/l	0.17	0.03	3/15/2006
pH (Laboratory)	EPA150.1	Std Units	7.6	N/A	3/14/2006
Total Kjeldahl Nitrogen	Attached	Attached	Completed	Attached	3/21/2006
Total Organic Carbon	Attached	Attached	Completed	Attached	3/20/2006
Total Phenol	Attached	Attached	Completed	Attached	3/24/2006
Total Suspended Solids	EPA160.2	mg/l	143	5	3/16/2006
Turbidity (Laboratory)	SM2130-B	NTU	200	0.05	3/14/2006
Zinc (Zn)	EPA200.8	ug/L	101	5	3/21/2006

Lab Number:

AA86885

Sample Site: Source Code: FRONT ST AT WEST ST

Sample ID:

Client Code:

Collection Date/Time: Submittal Date/Time:

3/14/2006 8:30 3/14/2006 12:39

Sample Collector:

ROMERO G

SOLEDA-W

Sample Comments:

Routine Storm Water. Dissolved Oxygen 10.4 mg/L.

Analyte	Method	Unit	Result	PQL	Date Analyzed
Ammonia(N)	EPA350.3	mg/l	0.17	0.05	3/17/2006
Coliform; Fecal	SM9221E	#/100 ml	1700	Variable	3/14/2006
Coliform; Total	SM9221B	#/100 ml	>=16000	Variable	3/14/2006
Conductivity	EPA120.1	umho/cm	116	3,541,347	3/14/2006
Copper (Cu)	EPA200.8	ug/L	ND	0.5	3/21/2006
Lead (Pb)	EPA200.8	ug/L	8 //	0.5	3/21/2006
MBAS surfactants	Subcontract	Attached	Completed	Attached	3/15/2006
NO3 (Nitrate)	EPA300	mg/L	2 (***)	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	3/14/2006
Oil & Grease	Subcontract	Attached	Completed	5	3/26/2006

mg/L: Milligrams per liter (=ppm) PQL: Practical Quantitation Limit

DLR: Detection Limit for Reporting

ug/L : Micrograms per liter (=ppb) MCL: Maximum Contaminant Level

*: Primary Standards ** : Secondary Standards

ND: Not Detected

N/A: Not Applicable

*** : Action Level

Orthophosphate as P	EPA365.2	mg/l	0.25	0.03	3/15/2006
pH (Laboratory)	EPA150.1	Std Units	7.5	N/A	3/14/2006
Total Kjeldahl Nitrogen	Attached	Attached	Completed	Attached	3/21/2006
Total Organic Carbon	Attached	Attached	Completed	Attached	3/20/2006
Total Phenol	Attached	Attached	Completed	Attached	3/24/2006
Total Suspended Solids	EPA160.2	mg/l	85	5	3/16/2006
Turbidity (Laboratory)	SM2130-B	NTU	200	0.05	3/14/2006
Zinc (Zn)	EPA200.8	ug/L	144	5 5	3/21/2006

AA86886 Lab Number:

Sample Site:

SAN VICENTE RD AT MARKET ST

Source Code: Sample ID:

Sample Comments:

Routine Storm Water. Dissolved Oxygen 10.2 mg/L.

Analyte	Method	Unit	Result	PQL	Date Analyzed
Ammonia(N)	EPA350.3	mg/l	0.20	0.05	3/17/2006
Coliform; Fecal	SM9221E	#/100 ml	5000	Variable	3/14/2006
Coliform; Total	SM9221B	#/100 ml	>=16000	Variable	3/14/2006
Conductivity	EPA120.1	umho/cm	116	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	3/14/2006
Copper (Cu)	EPA200.8	ug/L	ND THE PLANT	0.5	3/21/2006
Lead (Pb)	EPA200.8	ug/L	ND	0.5	3/21/2006
MBAS surfactants	Subcontract	Attached	Completed	Attached	3/15/2006
NO3 (Nitrate)	EPA300	mg/L	nu benzinasi san dalah ili meneli ND	Baladarina (Bara da da 1	3/14/2006
Oil & Grease	Subcontract	Attached	Completed	5	3/26/2006
Orthophosphate as P	EPA365.2	mg/l	0.15	0.03	3/15/2006
pH (Laboratory)	EPA150.1	Std Units	7.7	N/A	3/14/2006
Total Kjeldahl Nitrogen	Attached	Attached	Completed	Attached	3/21/2006
Total Organic Carbon	Attached	Attached	Completed	Attached	3/20/2006
Total Phenol	Attached	Attached	Completed	Attached	3/24/2006
Total Suspended Solids	EPA160.2	mg/l	26	- 5	3/16/2006
Turbidity (Laboratory)	SM2130-B	NTU	70	0.05	3/14/2006
Zinc (Zn)	EPA200.8	ug/L	ND ND	5.000	3/21/2006

AA86887 Lab Number:

Sample Site:

Source Code:

GABILAN DR AT TOLEDO ST

Sample ID:

Client Code:

Client Code:

Collection Date/Time:

Submittal Date/Time:

Sample Collector:

SOLEDA-W

SOLEDA-W

9:30

12:39

3/14/2006

3/14/2006

ROMERO G

Collection Date/Time: Submittal Date/Time:

3/14/2006 3/14/2006

10:15 12:39

Sample Collector:

ROMERO G

Routine Storm Water. Dissolved Oxygen 10.5 mg/L. Phenol not tested - incorrect sample container. Sample Comments:

Analyte	Method	Unit	Result	PQL	Date Analyzed
Ammonia(N)	EPA350.3	mg/l	0.09	0.05	3/17/2006

mg/L: Milligrams per liter (=ppm) PQL: Practical Quantitation Limit ug/L: Micrograms per liter (=ppb) MCL: Maximum Contaminant Level

*: Primary Standards **: Secondary Standards

*** : Action Level

DLR: Detection Limit for Reporting

ND: Not Detected

N/A: Not Applicable

Coliform; Fecal	SM9221E	#/100 ml	1400	Variable	3/14/2006
Coliform; Total	SM9221B	#/100 ml	9000	Variable	3/14/2006
Conductivity	EPA120.1	umho/cm	130	1	3/14/2006
Copper (Cu)	EPA200.8	ug/L	ND	0.5	3/21/2006
Lead (Pb)	EPA200.8	ug/L	ND ***	0.5	3/21/2006
MBAS surfactants	Subcontract	Attached	Completed	Attached	3/16/2006
NO3 (Nitrate)	EPA300	mg/L			3/14/2006
Oil & Grease	Subcontract	Attached	Completed	5	3/26/2006
Orthophosphate as P	EPA365.2	mg/l	0.11	0.03	3/15/2006
pH (Laboratory)	EPA150.1	Std Units	7.8	N/A	3/14/2006
Total Kjeldahl Nitrogen	Attached	Attached	Completed	Attached	3/21/2006
Total Organic Carbon	Attached	Attached	Completed	Attached	3/22/2006
Total Suspended Solids	EPA160.2	mg/l	7	5	3/16/2006
Turbidity (Laboratory)	SM2130-B	NTU	18	0.05	3/14/2006
Zinc (Zn)	EPA200.8	ug/L	ND	5	3/21/2006

Lab Number:

AA86888

Sample Site:

GABILAN DR AT PRADO DR

Source Code: Sample ID: Client Code:

Collection Date/Time:

SOLEDA-W 3/14/2006 10:55

Submittal Date/Time:

3/14/2006 12:39

Sample Collector: ROMERO G

Sample Comments:

Routine Storm Water. Dissolved Oxygen 9.0 mg/L. Phenol not tested - incorrect sample container.

Analyte	Method	Unit	Result	PQL	Date Analyzed
Ammonia(N)	EPA350.3	mg/l	0.51	0.05	3/17/2006
Coliform; Fecal	SM9221E	#/100 ml	130	Variable	3/14/2006
Coliform; Total	SM9221B	#/100 ml	>=16000	Variable	3/14/2006
Conductivity	EPA120.1	umho/cm	70	1.	3/14/2006
Copper (Cu)	EPA200.8	ug/L	ND	0.5	3/21/2006
Lead (Pb)	EPA200.8	ug/L	12	0.5	3/21/2006
MBAS surfactants	Subcontract	Attached	Completed	Attached	3/15/2006
NO3 (Nitrate)	EPA300	mg/L	V18 - 15 (18)		3/14/2006
Oil & Grease	Subcontract	Attached	Completed	5	3/26/2006
Orthophosphate as P	EPA365.2	mg/l	0.14	0.03	3/15/2006
pH (Laboratory)	EPA150.1	Std Units	7.4	N/A	3/14/2006
Total Kjeldahl Nitrogen	Attached	Attached	Completed	Attached	3/21/2006
Total Organic Carbon	Attached	Attached	Completed	Attached	3/23/2006
Total Suspended Solids	EPA160.2	mg/l	327	5 . 5. 5.	3/16/2006
Turbidity (Laboratory)	SM2130-B	NTU	350	0.05	3/14/2006
Zinc (Zn)	EPA200.8	ug/L	188	5	3/21/2006

mg/L: Milligrams per liter (=ppm)
PQL: Practical Quantitation Limit
DLR: Detection Limit for Reporting

ug/L: Micrograms per liter (=ppb)
MCL: Maximum Contaminant Level

*: Primary Standards
**: Secondary Standards

ND : Not Detected

N/A: Not Applicable

*** : Action Level

Report Approved by:

G. R. Guibert, M.S., P.H.M.

Laboratory Director

mg/L : Milligrams per liter (=ppm)
PQL : Practical Quantitation Limit

DLR: Detection Limit for Reporting

ug/L : Micrograms per liter (=ppb)

MCL : Maximum Contaminant Level ND : Not Detected N/A : N

* : Primary Standards

** : Secondary Standards

N/A : Not Applicable

*** : Action Level



BSK Submission Number: 2006031168

04/18/2006

Gerry Guibert Monterey CHD 1270 Natividad Rd. Rm A15 Salinas, CA 93906



Dear Gerry Guibert,

Thank you for selecting BSK Analytical Laboratories for your analytical testing needs. We have prepared this report in response to your request for analytical services. Please find enclosed the following sections for your complete laboratory report, each uniquely paginated:

CASE NARRATIVE: An overview of the work performed.
CERTIFICATE OF ANALYSIS: Analytical results.
REPORT OF SAMPLE INTEGRITY
CHAIN OF CUSTODY FORM
SUBCONTRACTED ANALYTICAL REPORT(S)

Certification: I certify that this data package is in compliance with NELAC Standards for applicable analyses under NELAP Certificate #04227CA, and is in compliance with ELAP Standards for applicable certified analyses under ELAP Certificate #1180, except for the conditions listed.

If additional clarification of any information is required, please contact your Client Services Representative, John Posten, at (800) 877-8310 or (559) 497-2888.

BSK ANALYTICAL LABORATORIES

Yohn Posteyl

Client Services Representative

BSK Submission Number: 2006031168

SAMPLE AND RECEIPT INFORMATION

The sample(s) was received, prepared, and analyzed within the method specified holding times unless otherwise noted on the Certificate of Analysis. Samples, when shipped, arrived within acceptable temperature requirements of 0° to 6° Celsius unless otherwise noted on the Report of Sample Integrity. Samples collected by BSK Analytical Laboratories were collected in accordance with the BSK Sampling and Collection Standard Operating Procedures.

QUALITY CONTROL

All analytical quality controls are within established method criteria except when noted in the Quality Control section or on the Certificate of Analysis. All positive results for EPA Methods 504.1, 502.2, and 524.2 require the analysis of a Field Reagent Blank (FRB) to confirm that the results are not a contamination error from field sampling steps. If Field Reagent Blanks were not submitted with the samples, this method requirement has not been performed. OC samples may include analytes not requested in this submission.

<u>run</u>	<u>ORDER</u>	<u>TEST</u>	ANALYT
109501	700983	SM 5540 C	MBAS, C

NALYTE COMMENT

MBAS, Calculated as LAS, MS and MSD recoveries were affected by the mol wt 340 matrix.

SAMPLE RESULT INFORMATION

Samples are analyzed as received (wet weight basis) unless noted here. The results relate only to the items tested. Any exceptions to be considered when evaluating these results are also listed here, if applicable. Results contained in this package shall not be reproduced, except in full, without written approval of BSK Analytical Laboratories.

ORDER TEST

ANALYTE

COMMENT



Gerry Guibert Monterey CHD 1270 Natividad Rd. Rm A15 Salinas, CA 93906

BSK Submission #: 2006031168 BSK Sample ID #: 699774

Project ID:

Project Desc: Soledad

Submission Comments:

Sample Type:

Liquid

Sample Description: Wastewater Side Sample Comments: AA86883

Certificate of Analysis NELAP Certificate #04227CA ELAP Certificate #1180



Report Issue Date: 04/18/2006

Date Sampled: 03/14/2006

Time Sampled: 0740
Date Received: 03/15/2006

Inorganics								
Analyte	Method	Result	Units	PQL	Dilution	DLR	Prep Date/Time	Analysis Date/Time
MBAS, Calculated as LAS, mol wt	340 SM 5540 C	0.087	mg/L	0.05	1	0.05	03/15/06 15:30	03/15/06 15:30
Nitrogen - Total Kjeldahl (TKN)	EPA 351.2	1.6	mg/L	1.0	1	1.0	03/21/06	03/27/06
Total Organic Carbon (TOC)	SM 5310-C	14	mg/L	0.2	1	0.2	03/20/06	03/20/06
Organics								
Analyte	Method	Result	Units	PQL	Dilution	DLR	Prep Date/Time	Analysis Date/Time
Total Oil and Grease	EPA 1664	2.9	mg/L	1.0	1	1.0	03/26/06	03/26/06

mg/L: Milligrams/Liter (ppm) mg/Kg: Milligrams/Kilogram (ppm) µg/L: Micrograms/Liter (ppb) µg/Kg: Micrograms/Kilogram (ppb) %Rec: Percent Recovered (surrogates)

PQL: Practical Quantitation Limit

DLR: Detection Limit for Reporting : PQL x Dilution

ND: None Detected at DLR pCi/L: Picocurie per Liter

H: Analyzed outside of hold time

P: Preliminary result

S: Suspect result. See Case Narrative for comments.

Gerry Guibert Monterey CHD 1270 Natividad Rd. Rm A15 Salinas, CA 93906

Certificate of Analysis NELAP Certificate #04227CA ELAP Certificate #1180



BSK Submission #: 2006031168

BSK Sample ID #: 699775

Project ID:

Project Desc: Soledad

Submission Comments:

Liquid

Sample Type: Sample Description: Front St at Nestles

Sample Comments: AA86884

Date Sampled: 03/14/2006

Time Sampled: 0800 Date Received: 03/15/2006

Inorganics								
Analyte	Method	Result	Units	PQL	Dilution	DLR	Prep Date/Time	Analysis Date/Time
MBAS, Calculated as LAS, mol wt	340 SM 5540 C	ND	mg/L	0.05	1	0.05	03/15/06 15:30	03/15/06 15:30
Nitrogen - Total Kjeldahl (TKN)	EPA 351.2	1.4	mg/L	1.0	1	1.0	03/21/06	03/27/06
Total Organic Carbon (TOC)	SM 5310-C	12	mg/L	0.2	1	0.2	03/20/06	03/20/06
Organics							.	
Analyte	Method	Result	Units	PQL	Dilution	DLR	Prep Date/Time	Analysis Date/Time
Total Oil and Grease	EPA 1664	3.7	mg/L	1.0	1	1.0	03/26/06	03/26/06

mg/L: Milligrams/Liter (ppm) mg/Kg: Milligrams/Kilogram (ppm) μg/L: Micrograms/Liter (ppb) μg/Kg: Micrograms/Kilogram (ppb) %Rec: Percent Recovered (surrogates)

Report Authentication Code:

PQL: Practical Quantitation Limit DLR: Detection Limit for Reporting

: PQL x Dilution

ND: None Detected at DLR pCi/L: Picocurie per Liter

H: Analyzed outside of hold time

P: Preliminary result

S: Suspect result. See Case Narrative for comments.

Gerry Guibert Monterey CHD 1270 Natividad Rd. Rm A15 Salinas, CA 93906

BSK Submission #: 2006031168

BSK Sample ID #: 699776

Project ID:

Project Desc: Soledad

·

Submission Comments: Sample Type: Lie

Liquid

Sample Description: Front St at West St Sample Comments: AA86885 Date Sampled: 03/14/2006 Time Sampled: 0830

Certificate of Analysis NELAP Certificate #04227CA

ELAP Certificate #1180

Date Received: 03/15/2006 Inorganics Prep Analysis Analyte Method Result Units PQL Dilution DLR Date/Time Date/Time MBAS, Calculated as LAS, mol wt 340 SM 5540 C ND 0.05 03/15/06 15:30 03/15/06 15:30 mg/L 0.05 Nitrogen - Total Kjeldahl (TKN) EPA 351.2 ND mg/L 1.0 1 1.0 03/21/06 03/27/06 Total Organic Carbon (TOC) SM 5310-C 6.4 mg/L 0.2 0.2 03/20/06 03/20/06 **Organics** Prep Date/Time Analysis Analyte PQL Dilution Method Result Units DLR Date/Time Total Oil and Grease EPA 1664 1.3 mg/L 1.0 1.0 03/26/06 03/26/06

mg/L: Milligrams/Liter (ppm) mg/Kg: Milligrams/Kilogram (ppm) μg/L: Micrograms/Liter (ppb) μg/Kg: Micrograms/Kilogram (ppb) %Rec: Percent Recovered (surrogates)

Report Authentication Code:

PQL: Practical Quantitation Limit DLR: Detection Limit for Reporting

: PQL x Dilution

ND: None Detected at DLR

pCi/L: Picocurie per Liter

H: Analyzed outside of hold time

P: Preliminary result

S: Suspect result. See Case Narrative for comments.

Gerry Guibert Monterey CHD 1270 Natividad Rd. Rm A15 Salinas, CA 93906

Certificate of Analysis NELAP Certificate #04227CA **ELAP Certificate #1180**



Report Issue Date: 04/18/2006

BSK Submission #: 2006031168 BSK Sample ID #: 699777

Project ID:

Project Desc: Soledad

Submission Comments: Sample Type:

Liquid

Sample Description: San Vicente Rd at Market St

Sample Comments: AA86886

Date Sampled: 03/14/2006

Time Sampled: 0900 Date Received: 03/15/2006

Inorganics Analyte	Method	Result	Units	PQL	Dilution	DLR	Prep Date/Time	Analysis Date/Time
MBAS, Calculated as LAS, mol wt	340 SM 5540 C	0.12	mg/L	0.05	1	0.05	03/15/06 15:30	03/15/06 15:30
Nitrogen - Total Kjeldahl (TKN)	EPA 351.2	ND	mg/L	1.0	1	1.0	03/21/06	03/27/06
Total Organic Carbon (TOC)	SM 5310-C	13	mg/L	0.2	1	0.2	03/20/06	03/20/06
Organics								
Analyte	Method	Result	Units	PQL	Dilution	DLR	Prep Date/Time	Analysis Date/Time
Total Oil and Grease	EPA 1664	3.0	mg/L	1.0	1	1.0	03/26/06	03/26/06

mg/L: Milligrams/Liter (ppm) mg/Kg: Milligrams/Kilogram (ppm) μg/L: Micrograms/Liter (ppb) μg/Kg: Micrograms/Kilogram (ppb) %Rec: Percent Recovered (surrogates) PQL: Practical Quantitation Limit DLR: Detection Limit for Reporting

: PQL x Dilution

ND: None Detected at DLR pCi/L: Picocurie per Liter

- H: Analyzed outside of hold time
- P: Preliminary result
- S: Suspect result. See Case Narrative for comments.
- E: Analysis performed by External laboratory. See External Laboratory Report attachments.

Gerry Guibert Monterey CHD 1270 Natividad Rd. Rm A15 Salinas, CA 93906

BSK Submission #: 2006031168 BSK Sample ID #: 699778

Project ID:

Project Desc: Soledad

Submission Comments:

Sample Type:

Liquid

Sample Description: Gabilan Dr at Toledo St

Sample Comments: AA86887

Certificate of Analysis NELAP Certificate #04227CA ELAP Certificate #1180



Date Sampled: 03/14/2006 Time Sampled: 1614

Date Received: 03/15/2006

Inorganics								
Analyte	Method	Result	Units	PQL	Dilution	DLR	Prep Date/Time	Analysis Date/Time
MBAS, Calculated as LAS, mol wt	340 SM 5540 C	0.26	mg/L	0.05	1	0.05	03/16/06 09:30	03/16/06 09:30
Nitrogen - Total Kjeldahl (TKN)	EPA 351.2	ND	mg/L	1.0	1	1.0	03/21/06	03/27/06
Total Organic Carbon (TOC)	SM 5310-C	6.7	mg/L	0.2	1	0.2	03/22/06	03/22/06
Organics							.	4 7 .
Analyte	Method	Result	Units	PQL	Dilution	DLR	Prep Date/Time	Analysis Date/Time
Total Oil and Grease	EPA 1664	1.0	mg/L	1.0	1	1.0	03/26/06	03/26/06

mg/L: Milligrams/Liter (ppm) mg/Kg: Milligrams/Kilogram (ppm) μg/L: Micrograms/Liter (ppb) μg/Kg: Micrograms/Kilogram (ppb) %Rec: Percent Recovered (surrogates) PQL: Practical Quantitation Limit DLR: Detection Limit for Reporting

: PQL x Dilution

ND: None Detected at DLR

pCi/L: Picocurie per Liter

H: Analyzed outside of hold time

P: Preliminary result

S: Suspect result. See Case Narrative for comments.

Gerry Guibert Monterey CHD 1270 Natividad Rd. Rm A15 Salinas, CA 93906

BSK Submission #: 2006031168 BSK Sample ID #: 699779

Project ID:

Project Desc: Soledad

Submission Comments:

Sample Type:

Liquid

Sample Description: Gabilan Dr at Prado Dr

Sample Comments: AA86888

Certificate of Analysis NELAP Certificate #04227CA ELAP Certificate #1180



Report Issue Date: 04/18/2006

Date Sampled: 03/14/2006 Time Sampled: 1035

Date Received: 03/15/2006

Inorganics								4
Analyte	Method	Result	Units	PQL	Dilution	DLR	Prep Date/Time	Analysis Date/Time
MBAS, Calculated as LAS, mol wt	340 SM 5540 C	ND	mg/L	0.05	1	0.05	03/15/06 15:30	03/15/06 15:30
Nitrogen - Total Kjeldahl (TKN)	EPA 351.2	1.6	mg/L	1.0	1	1.0	03/21/06	03/27/06
Total Organic Carbon (TOC)	SM 5310-C	8.0	mg/L	0.2	1	0.2	03/23/06	03/23/06
Organics								
Analyte	Method	Result	Units	PQL	Dilution	DLR	Prep Date/Time	Analysis Date/Time
Total Oil and Grease	EPA 1664	2.6	mg/L	1.0	1	1.0	03/26/06	03/26/06

mg/L: Milligrams/Liter (ppm) mg/Kg: Milligrams/Kilogram (ppm) μg/L: Micrograms/Liter (ppb) μg/Kg: Micrograms/Kilogram (ppb) %Rec: Percent Recovered (surrogates) PQL: Practical Quantitation Limit DLR: Detection Limit for Reporting

: PQL x Dilution

ND: None Detected at DLR pCi/L: Picocurie per Liter


H: Analyzed outside of hold time

P: Preliminary result

S: Suspect result. See Case Narrative for comments.

E: Analysis performed by External laboratory. See External Laboratory Report attachments.

Page 6 of 6



LABORATORY REPORT

Prepared For:

BSK Labs

Project: 2006031168

1414 Stanislaus Street Fresno, CA 93706 Attention: John Posten

Sampled: 03/14/06 Received: 03/17/06 Issued: 03/28/06 14:17

135ucu. 03/26/00 14.1

NELAP #01108CA California ELAP#1197 CSDLAC #10117

The results listed within this Laboratory Report pertain only to the samples tested in the laboratory. The analyses contained in this report were performed in accordance with the applicable certifications as noted. All soil samples are reported on a wet weight basis unless otherwise noted in the report. This Laboratory Report is confidential and is intended for the sole use of Del Mar Analytical and its client. This report shall not be reproduced, except in full, without written permission from Del Mar Analytical. The Chain of Custody, 1 page, is included and is an integral part of this report.

This entire report was reviewed and approved for release.

CASE NARRATIVE

SAMPLE RECEIPT:

Samples were received intact, at 4°C, on ice and with chain of custody documentation.

HOLDING TIMES:

All samples were analyzed within prescribed holding times and/or in accordance with the Del Mar

Analytical Sample Acceptance Policy unless otherwise noted in the report.

PRESERVATION:

Samples requiring preservation were verified prior to sample analysis.

QA/QC CRITERIA:

All analyses met method criteria, except as noted in the report with data qualifiers.

COMMENTS:

No significant observations were made.

SUBCONTRACTED:

No analyses were subcontracted to an outside laboratory.

LABORATORY ID	CLIENT ID	MATRIX
IPC2291-01	699774 Wastewater Side	Liquid
IPC2291-02	699775 Front St at Nestles	Liquid
IPC2291-03	699776 Front St at West St	Liquid
IPC2291-04	699777 San Vicente Rd at Market St	Liquid

Reviewed By:

Del Mar Analytical - Irvine

Misi Raghtley

Lisa Reightley Project Manager



BSK Labs

Project ID: 2006031168

1414 Stanislaus Street Fresno, CA 93706 Attention: John Posten

Report Number: IPC2291

Sampled: 03/14/06 Received: 03/17/06

INORGANICS

INORGANICS											
Analyte	Method	Batch	Reporting Limit	Sample Result	Dilution Factor	Date Extracted	Date Analyzed	Data Qualifiers			
Sample ID: IPC2291-01 (699774 Wastev Reporting Units: mg/l	vater Side - Liquid)										
Phenols	EPA 420.1	6C24117	0.10	ND	1	3/24/2006	3/25/2006				
Sample ID: IPC2291-02 (699775 Front S Reporting Units: mg/l	st at Nestles - Liquid)										
Phenols	EPA 420.1	6C24117	0.10	ND	1	3/24/2006	3/25/2006				
Sample ID: IPC2291-03 (699776 Front S Reporting Units: mg/l	t at West St - Liquid)										
Phenols	EPA 420.1	6C24117	0.10	ND	1	3/24/2006	3/25/2006				
Sample ID: IPC2291-04 (699777 San Vicente Rd at Market St - Liquid)											
Reporting Units: mg/l Phenols	EPA 420.1	6C24117	0.10	ND	1	3/24/2006	3/25/2006				



17461 Derian Ave., Suite 100, Irvine, CA 92614 (949) 261-1022 FAX (949) 260-3297 1014 E. Cooley Dr., Suite A, Colton, CA 92324 (909) 370-4667 FAX (909) 370-1046 9830 South 51st St., Suite B-120, Phoenix, AZ 85044 (480) 785-0043 FAX (480) 785-0851 2520 E. Sunset Rd. #3, Las Vegas, NV 89120 (702) 798-3620 FAX (702) 798-3621

BSK Labs

Project ID: 2006031168

1414 Stanislaus Street Fresno, CA 93706 Attention: John Posten

Report Number: IPC2291

Sampled: 03/14/06 Received: 03/17/06

METHOD BLANK/QC DATA

INORGANICS

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Data Qualifiers
Batch: 6C24117 Extracted: 03/24/06										
Blank Analyzed: 03/25/2006 (6C24117-B	LK1)									
Phenols	ND	0.10	mg/l							
LCS Analyzed: 03/25/2006 (6C24117-BS	1)									
Phenols	0.505	0.10	mg/l	0.500		101	90-110			
Matrix Spike Analyzed: 03/25/2006 (6C2	4117-MS1)				Source: IP	C2291-01	[
Phenols	0.517	0.10	mg/l	0.500	ND	103	65-155			
Matrix Spike Dup Analyzed: 03/25/2006 (6C24117-MSD1)						C2291-01	Į			
Phenols	0.501	0.10	mg/l	0.500	ND	100	65-155	3	20	



17461 Derian Ave., Suite 100, Irvine, CA 92614 (949) 261-1022 FAX (949) 260-3297 1014 E. Cooley Dr., Suite A, Collon, CA 92324 (909) 370-4667 FAX (909) 370-1046 9830 South 51st St., Suite B-120, Phoenix, AZ 85044 (480) 785-0043 FAX (480) 785-0851 2520 E. Sunset Rd. #3, Las Vegas, NV 89120 (702) 798-3620 FAX (702) 798-3621

BSK Labs

Project ID: 2006031168

1414 Stanislaus Street Fresno, CA 93706 Attention: John Posten

Report Number: IPC2291

Sampled: 03/14/06 Received: 03/17/06

DATA QUALIFIERS AND DEFINITIONS

ND

Analyte NOT DETECTED at or above the reporting limit or MDL, if MDL is specified.

RPD Relative Percent Difference



17461 Derian Ave., Suite 100, Irvine, CA 92614 (949) 261-1022 FAX (949) 260-3297 1014 E. Cooley Dr., Suite A, Colton, CA 92324 (909) 370-4667 FAX (909) 370-1046 9830 South 51st St., Suite B-120, Phoenix, AZ 85044 (480) 785-0043 FAX (480) 785-0851 2520 E. Sunset Rd. #3, Las Vegas, NV 89120 (702) 798-3620 FAX (702) 798-3621

BSK Labs

Project ID: 2006031168

1414 Stanislaus Street Fresno, CA 93706 Attention: John Posten

Report Number: IPC2291

Sampled: 03/14/06 Received: 03/17/06

Certification Summary

Del Mar Analytical - Irvine

Method Matrix

Nelac

California

EPA 420.1

Water

X

X

Nevada and NELAP provide analyte specific accreditations. Analyte specific information for Del Mar Analytical may be obtained by contacting the laboratory or visiting our website at www.testamericainc.com

Del Mar Analytical - Irvine Lisa Reightley Project Manager